

TECHNICAL DATA SHEET SELF-RETRACTING LIFELINE



Prod. No. : V845533010LE
Mod. No. : SRL-53302-10LE



DESCRIPTION

Leading Edge self-retracting lifeline in a durable aluminum housing with galvanized steel wire cable. Approved for use in vertical and horizontal applications.

SPECIFICATIONS

Material: 5mm (3/16") galvanized cable

Length: 10' (3 m)

Number of Workers: 1

Weight: 4.2 lb (1.9 kg)

Capacity: 300 lb (136 kg) for one worker (combined weight of person, tools, clothing, etc)

Operating Temperature: -35° C to +35° C

ATTACHMENT POINTS

Swivel eye on housing with carabiner for attachment to anchorage connector and double action locking snap hook with fall indicator on galvanized wire cable for connection to dorsal D-ring.

STANDARDS

Compliance: Certified to CSA Z259.2.2-98 and ANSI Z359.14 (Class B maximum arrest distance 54" (1,372 mm), average arrest force 900 lb (4 kN), maximum arrest force 1,350 lb (6 kN))

COMPONENT COMPATIBILITY

Are designed for use with PeakWorks approved components or subsystems (full body harnesses, anchorage connectors, etc.) or as recommended by a qualified person.

WARNINGS

See operating and maintenance instruction manual for details.

STORAGE

Store in a cool dry place away from chemicals, water, corrosive environments, and sources of heat or spark.