


OSG PHOENIX® PSF

90° Shoulder Cutter

List 52900

PSF SA/FA (Inch)




| EDP No. | Body Type | Teeth Type | Designation | Type | Tool Dia. (inch) | No. of Teeth | Shank Dia. (inch) | Overall Length (inch) | Neck Length (inch) | Applicable Insert |
|----------|-------------------------|------------|-------------------|------|------------------|--------------|-------------------|-----------------------|--------------------|-------------------|
| | | | | | D | | d | L | L1 | |
| 52900000 | Cylindrical Shank Short | Normal | PSF09R100SA100-3S | 1 | 1.000 | 3 | 1.000 | 4.724 | 1.378 | SD_T09... |
| 52900001 | | | PSF09R125SA125-4S | 1 | 1.250 | 4 | 1.250 | 5.118 | 1.772 | |
| 52900002 | | | PSF09R150SA125-5S | 2 | 1.500 | 5 | 1.250 | 5.512 | 1.969 | |
| 52900004 | Weldon Shank Short | Normal | PSF09R100FA100-3S | 1 | 1.000 | 3 | 1.000 | 3.831 | 1.551 | |
| 52900005 | | | PSF09R125FA125-4S | 1 | 1.250 | 4 | 1.250 | 4.378 | 2.098 | |
| 52900006 | | | PSF09R150FA125-5S | 2 | 1.500 | 5 | 1.250 | 4.378 | 2.098 | |

Packed: 1 pc.



List 78030

PSF SS (Metric)



| EDP No. | Body Type | Teeth Type | Designation | Type | Tool Dia. (mm) | No. of Teeth | Shank Dia. (mm) | Overall Length (mm) | Neck Length (mm) | Applicable Insert |
|---------|-------------------------|------------|------------------|------|----------------|--------------|-----------------|---------------------|------------------|-------------------|
| | | | | | D | | d | L | L1 | |
| 7803001 | Cylindrical Shank Short | Normal | PSF09R025SS25-3S | 1 | 25 | 3 | 25 | 120 | 35 | SD_T09... |
| 7803002 | | | PSF09R032SS32-4S | 1 | 32 | 4 | 32 | 130 | 45 | |
| 7803003 | | | PSF09R040SS32-5S | 2 | 40 | 5 | 32 | 140 | 50 | |

Packed: 1 pc.

Note: **This item is stocked overseas. Please contact OSG for availability and delivery.**

