







PAK565 Holds (2) 55 gal. Plastic or Steel Drums, 26" x 52" x 5.75", 22 gal. Sump Capacity

Manage small leaks and drips that mess up your floor and containers with tough New Pig decks.

- The strongest drip decks you can buy won't buckle or bow. Guaranteed for life.
- Low-profile 5.75"H design is easy to load or unload; pumps and funnels are easy to access
- Molded-in sump catches leaks, drips and spills to help keep your storage areas clean and safe
- Low-density polyethylene (LDPE) construction resists UV rays, rust, corrosion and most chemicals
- Textured grating adds traction and lifts out for easy sump access
- Translucent white sidewalls allow easy visual inspection
- We test all of our PIG Containment Deck designs at max load for months to ensure they can handle full capacity at your facility



Specifications

| Holds | (2) 55 gal. Plastic or Steel Drums |
|-----------------------|---|
| Color | Black/White |
| Dimensions | 26" W x 52" L x 5.75" H |
| Recycled Content | 43% Post-Industrial Recycled Polyethylene |
| Load Capacity UDL | 3000 lbs. |
| Sump Capacity | 22 gal. |
| Double-Stackable Unit | No |
| Drain | None |
| Fork Truck Access | No Fork Truck Access |
| Grates | (1) 48" L x 24" W Grate |
| Use With Flammables | No |
| Sold as | 1 each |
| Weight | 40 lbs. |
| # per Pallet | 20 |
| Composition | Sump - LDPE w/ UV Inhibitor |

| | Grate - Polyethylene |
|----------------------|----------------------|
| UNSPSC | 24101905 |
| Pigalog® Page Number | Page 373 |

Metric Equivalent

| Dimensions | 66cm W x 132.1cm L x 14.6cm H |
|-------------------|-------------------------------|
| Load Capacity UDL | 1360.8 kg |
| Sump Capacity | 83.3 L |
| Weight | 18.1 kg |

Technical Information

Technical Documents

LDPE Products

40 CFR 112.7

40 CFR 122.26

40 CFR 264.175

Disclaimers

Flammables Notice

If using this product with flammable liquids, please consider the regulations that apply to storage and handling of flammable liquids and the safety of this application, specifically flammable vapors, static discharge and heat sources. For further assistance, please call Technical Services.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com