

## PIG® Roof Leak Diverter

TLS463 Roofs, Diverter Only, 7' x 7'

Stop devastating roof leak damage and protect your people, equipment and inventory with the original diverter. Invented here!



- The original Leak Diverter - invented here and engineered to stop devastating roof leak damage every time, guaranteed
- Hangs easily in problem spots to catch nuisance leaks and channel them to a floor drain or collection container
- Ideal for quick response to avoid downtime after a roof leak or for long-term prevention in leak-prone areas
- Nonpermeable tarp is vinyl coated for strength and durability; resists punctures, UV and mildew for long life
- Pinched corners help funnel liquid toward center for better drainage
- Accepts a standard 3/4" hose connection to channel liquid to floor drain or collection container (hose sold separately)
- Flow rate of 3.33 gallons per minute when used with a 1/2" ID hose
- Grommets resist tearing and make installation easy
- Need a custom size or solution? Just call 1-800-HOT-HOGS (468-4647)



| Item#     | Description  | Dimensions  | Weight    |
|-----------|--------------|-------------|-----------|
| TLS463-TR | Translucent, | 7' W x 7' L | 5.27 lbs. |
| TLS463-GY | Gray,        | 7' W x 7' L | 5.27 lbs. |
| TLS463-CL | Clear,       | 7' W x 7' L | 5.27 lbs. |

### Metric Equivalent:

| Item#     | Description  | Dimensions      | Weight |
|-----------|--------------|-----------------|--------|
| TLS463-TR | Translucent, | 2.1m W x 2.1m L | 2.4 kg |
| TLS463-GY | Gray,        | 2.1m W x 2.1m L | 2.4 kg |
| TLS463-CL | Clear,       | 2.1m W x 2.1m L | 2.4 kg |

### Specifications

Style

Diverter Only

|                                |  |
|--------------------------------|--|
| <b>Dimensions</b>              | 7' W x 7' L  |
| <b>Drainage Hose Included</b>  | No   |
| <b>Hanging Straps Included</b> | No   |
| <b>Hose Connector</b>          | .75"   |
| <b>Installation Method</b>     | Hanging Straps   |
| <b>Shape</b>                   | Square   |
| <b>Sold as</b>                 | 1 each   |
| <b>Weight</b>                  | 5.27 lbs.  |
| <b># per Pallet</b>            | 288  |
| <b>Composition</b>             | Diverter (Colors) - PVC, Polyester<br>Leak Diverter (Clear) - PVC w/ Polyester Reinforcement |
| <b>Application</b>             | Roofs  |
| <b>Flow Rate</b>               | 3.33 gal. per Minute   |
| <b>UNSPSC</b>                  | 24141506   |
| <b>Pigalog® Page Number</b>    | <a href="#">Page 263</a>   |

## Metric Equivalent

|                   |                 |
|-------------------|-----------------|
| <b>Dimensions</b> | 2.1m W x 2.1m L |
| <b>Weight</b>     | 2.4 kg          |

## Technical Information

### Technical Documents

[Instructions for Assembling PIG® Leak Diverter System](#)

[White paper – Slip & Fall Prevention Secrets](#)

### Disclaimers

#### Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.

#### Nominal Leak Diverter Dimensions

Dimensions are nominal size due to pinched corners and reinforced side walls.



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)