



# NEW PRODUCT ANNOUNCEMENT

Arrives  
September 15, 2021

## THE DEFENDER® FR /ARC ANTISTATIC RAINWEAR

### Common Features:

- Flame-Gard FR/ ARC tri-laminate material: top layer woven, middle layer membrane, bottom layer knit
  - Top layer: 300D Oxford non-conducting lattice - anti-static (98% polyester + 2% anti-static)
  - Middle layer: Flame-retardant PU moisture-permeable white glue
  - Bottom layer: Flame-retardant 60% modacrylic, 40% cotton
- Provides 4 levels of safety: 1) 100% waterproof, 2) FR, 3) ARC, and 4) anti-static protection
- Meets FR ASTM F1891-19 standard specifications for Arc and Flame-Resistant Rainwear
- ARC 2 rating: ATPV 11 cal/cm², EBTAS 19 cal/cm², HAF 73%
- NFPA 70E-18 and CSA Z462-18
- Meets CGSB 155.20-2017 Workwear for Protection Against Hydrocarbon Flash Fire – FR Rainwear Standard
- TPP: 12.3 cal/cm² Heavy-duty tear- and abrasion-resistant construction
- All critical seams double-stitched and heat-sealed with TPU seam tape.
- Full 100% FR cotton inner lining
- Navy bottom to reduce appearance of soiling
- StarTech® FR tape
- Sizes S - 5XL

### Jackets:

- CSA Z96-15 Class 2 Level 2 (becomes Class 3 when worn with Hi-Viz pant featuring reflective leg bands)
- ANSI/ISEA 107-2020 Class 3 Type P and R
- 2 lower pockets with flap closure
- 2 pen slots right side, 1 concealed chest FR zipper cell pocket on left side
- Stand-up protective collar with chin guard
- Radiophone clip strap
- Full front 2-way FR brass zipper with storm flap
- Adjustable draw-cord waist
- Adjustable storm cuffs
- 3-pc multi-adjustable hood

### Bib Pants:

- CSA Z96-15 Class 3 Level 2 (when worn with Hi-Viz Class 2 Level 2 Jacket)
- ANSI/ISEA 107-2020 Class E Supplemental type
- Heavy-duty adjustable elastic suspenders
- 2 chest pockets – with flap closer on right side
- Radiophone clip strap
- Full front 2-way FR brass zipper with storm flap
- 2 lower slash pockets, 2 back pockets, 1 tool pocket, 1 hammer loop
- 18" FR boot-access zippers

FLAME-GARD®

STAR-TECH FR  
Reflective Material  
Matériau réfléchissant

ARC GARD®

ARC 2



4484  
(V2590150)



4485  
(V2590160)

4486  
(V2590250)

4487  
(V2590260)



Brand

surewerx.com



Anti-static



EN ISO 11611-2015  
A1A2



EN ISO 11612-2015  
A1A2 B1 C1 F1



EN 1149-5:2008