## HI-VIS FLASH-GARD® FR/ARC-RATED INSULATED WATERPROOF BIB PANTS - HI-VIS ORANGE - M



Product # V3521750-M | Model # 5885

Premium FR/ARC insulated bib oversalls that offer the comfort workers need with the protection they demand. With permanent flame-resistant properties and full functionality in mind, you can focus on the job at hand knowing you are safe from harsh weather extremes and potentially hazardous work environments.

- Waterproof and windproof design stands up to the harshest weather conditions
- RF heat-welded seams deliver a highly durable, tear-resistant and leakproof design
- 4-way stretch fabric provides greater elasticity and maximum range of motion
- Premium StarTech® reflective tape provides maximum visibility even in low-lit working conditions
- Oil and chemical resistant material designed to offer added protection from job-related hazards
- Side adjustment feature on waist allows options for a tighter or looser fit
- FR elastic suspenders with adjustment buckle and spreader bar provide a comfortable fit
- · Convenient storage pocket for tools and personal effects
- Adjustable leg cuffs with snaps provide snug fit to work boots





## **TECHNICAL SPECIFICATIONS**

Adjustment Waist Tab Туре

Adjustment For Fit| Hook and Loop Tab Closure on Leg

Attributes Abrasion and

Tear Resistant| Acid Resistant| Chemical Resistant Fire Resistant Insulated Lined| Waterproof| Windproof

ANSI/ISEA Certification

107-2020

Class E Supplemental Type| CSA Z96-22 Class 3 Level 2 when worn with Class 2 Level 2 Jacket

Closure Type

Elastic

Colour Hi-Vis Orange

Quilted Fabric Туре

FR/ARC Standards ARC 4| ASTM

1959M-14| APTV 51 cal/cm²| EBT 57 cal/cm²| HAF 94%| CGSB 155.20-2017| ASTM F1891-19| ASTM F2733-17|

TPP 23.1

cal/cm<sup>2</sup> Gender Unisex Lining Material 100% FR Cotton 6.5 oz.

Lining Thickness

Lining Type Quilted

Cotton Material Polyurethane Coating

12 oz (400 GSM) Material Thickness

Number of Pockets

Pocket Inside Bib Туре Hook and Loop Closure

Reflective StarTech® FR| 4" Tape

Silver/Yellow Combined Performance meets BC/DOT configuration

Size