

# SPECIFICATION SHEET 100-333000

# CLEANTEAM® SINGLE USE CLASS 100 CLEANROOM NITRILE GLOVE WITH FULLY TEXTURED GRIP - 12"

- Exceed standards required for use in class 100 and other controlled environments
- Fully textured provides a good grip in wet or dry environments
- Ambidextrous for quick and easy donning
- Powder-Free to reduce allergic reactions
- Chlorinated to harden and cleanse the surface of the glove
- Electrostatic Dissipative (ESD) for improved performance in electronics assembly
- Beaded cuff adds additional strength to cuff edge for longer glove life and prevents liquid run-off

# **APPLICATIONS**

- Biotechnology
- Medical device manufacturing
- · Computer assembly

### **TECHNICAL DATA**

MATERIAL	100 % Nitrile				
COLOR	Natural				
CUFF STYLE	Beaded Cuff				
SIZES	S - XL				
PACKAGING	100 per bag; 10 bags per carton (1,000 pcs)				
CASE	12.4" x 12.4" x 12.4" / 31.5cm x 31.5cm x 31.5cm				
CASE	S M L XL				
WEIGHT	19 lbs / 8.6 kg	19.4 lbs / 8.8 kg	20.5 lbs / 9.3 kg	20.9 lbs / 9.5 kg	
C00	Malaysia				

### **PERFORMANCE PROPERTIES**

Protein Content (ug/g) ASTM D5712-05: 50 (max) Powder Content (mg/g) ASTM D 6124-01: 2 (max)

## **Elongation Information:**

BEFORI	AGING	AFTER ACCELERATED AGING		
Tensile Strength (minimum)	Elongation (minimum)	Tensile Strength (minimum)	Elongation (minimum)	
(Mpa)	%	(Mpa)	%	
14	600	14	500	

Partical Count - (IES - RP - C005.3): Count per cm<sup>2</sup> = <1200

### Ionic Burden (mg/cm²):

ANIONS			CATIONS			
CI	NO <sub>3</sub> <sup>2</sup>	SO <sub>4</sub> 2-	CA <sup>2+</sup>	MG <sup>2+</sup>	K <sup>+</sup>	NA <sup>2+</sup>
< 0.20	< 0.40	< 0.05	< 0.5	< 0.01	< 0.05	< 0.05

Non-volatile residue (Hexane extraction) ug/cm<sup>2</sup>: < 10 Silicone oil presence by FTIR (Hexane extraction): Absent

## **Quality Assurance Standard:**

Random Sampling based on ISO 2859	Character	Dimension	Physical Properties	Water Tight	Visual Defect (major)	Visual Defect (minor)
	Inspection Level	S - 2	S - 2	G 1	G 1	G 1
2009	AQL	4.0	4.0	1.5	2.5	4.0



### **BARCODES**

ITEM	BAG	DOZEN	CASE
□ 100-333000/S	01616314016660		02616314016660
□ 100-333000/M	01616314016677		02616314016677
□ 100-333000/L	01616314016684		02616314016684
□ 100-333000/XL	01616314016691		02616314016691

### **DIMENSIONS** (in/cm)

			M		XL
	A	12 / 30.5	12 / 30.5	12 / 30.5	12 / 30.5
ı	В	3.3 (+/1) / 8.3 (+/3)	3.7 (+/1) / 9.5 (+/3)	4.2 (+/1) / 10.6 (+/3)	4.4 (+/1) / 11.2 (+/3)

Palm Thickness: 0.12 mm (+/-0.02) Cuff Thickness: 0.08 mm (+/-0.02) Finger Tip Thickness: 0.18 mm (+/-0.02)

