



# SPECIFICATION SHEET

## 120-4200



### MAXIMUM SAFETY® REINFORCED GOATSKIN LEATHER PALM GLOVE

- Reinforced goatskin leather palm and back provides the softest, most abrasion-resistant leather and is highly recommended for applications requiring tactile sensitivity
- Split goatskin leather fingertips for added protection
- Internal foam padded palm absorbs and dampens shock
- TPR (Thermo Plastic Rubber) molded knuckle guards
- Reflective knuckle tape makes product easy to see in low light
- Nylon spandex fabric for comfort and breathability
- Micro cotton thumb for comfort
- Hook & loop closure for easy on/off and a secure fit
- Sandy PVC thumb crotch and thumb reinforcement
- Retail Ready

### APPLICATIONS

- Construction
- Auto repair
- Demolition
- Manufacturing
- Mining
- Fabrication
- Landscaping

### CARE INSTRUCTIONS

Machine wash in cold water. Do not bleach. Hang dry; tumble dry is not recommended. Do not iron.

### TECHNICAL DATA

MATERIAL	Leather / Spandex / Lycra
CONSTRUCTION	<b>Back:</b> Unlined spandex fabric (96% nylon, 4% spandex) <b>Palm:</b> Goatskin leather, 0.7 - 0.8 gauge <b>Fingers:</b> Heavy lycra fabric (94% nylon, 6% lycra) <b>Knuckles:</b> Vinyl TPR mold
COLOR	■ Brown / ■ Black
CUFF STYLE	Hook and loop wrist closure
SIZES	S - XXL
PACKAGING	12 pairs per dozen, 6 dozen per case
CASE	22.8" x 15.7" x 9.8" / 50cm x 38cm x 38cm
CASE WEIGHT	21.6 lbs / 9.8 kg
COO	Pakistan

### PERFORMANCE PROPERTIES

EN388: 2112						
ABRASION	0	1	2	3	4	-
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-

### BARCODES

ITEM	BAG	DOZEN	CASE
■ 120-4200/S	616314069321	01616314069320	02616314069329
■ 120-4200/M	616314069314	01616314069313	02616314069312
■ 120-4200/L	616314069307	01616314069306	02616314069305
■ 120-4200/XL	616314069338	01616314069337	02616314069336
■ 120-4200/XXL	616314069345	01616314069344	02616314069343



### DIMENSIONS (in/cm)

	S	M	L	XL	XXL
<b>A</b>	9 / 22.9	9.4 / 23.9	9.75 / 24.8	10.15 / 25.8	10.35 / 26.3
<b>B</b>	3.75 / 9.5	4 / 10.2	4.25 / 10.8	4.5 / 11.4	4.75 / 12.1

Tolerance (in): +/- 0.125

