

SPECIFICATION SHEET







MAXICHEM® NITRILE BLEND COATED **GLOVE WITH NYLON / LYCRA LINER AND NON-SLIP GRIP - 14"**

- Chemical resistance delivered through the ATG® LiquiTech® technology platform
- · Ultra lightweight synthetic coating combined with an industry leading super light seamless knit liner
- Tailored cuff, keeping the cuff close to your hand so maintaining your fingers at the tip of the glove
- Micro-cup non-slip grip finish allows for a controlled and superior grip in oily and wet applications
- This glove has been laundered prior to final packaging
- All ingredients used in the manufacturing and construction of this product are compliant with the REACH legislation

APPLICATIONS

- · Automotive assembly
- Chemical handling
- · Oil and gas
- General maintenance
- Metal fabrication

CARE INSTRUCTIONS

Use commercial laundry soap or detergent (do NOT use dry cleaning solutions) Wash in warm to medium hot water, do not exceed 104°F (40° C). Wash for 10 minutes and rinse in cold water. Repeat wash and rinse if soiling is especially heavy. Tumble dry - maximum temperature 140°F (60° C)

TECHNICAL DATA

MATERIAL	Nitrile, nylon, Lycra®				
COLOR	Shell: ■ Green / Grip: ■ Black				
CUFF STYLE	Gauntlet cuff				
SIZES	S - XXL				
PACKAGING	12 pairs per dozen, 6 dozen per case				
CASE	20.8" x 11.8" x 10.8" / 50.8cm x 30.0cm x 27.4cm				
CASE	S	M	L	XL	XXL
WEIGHT	20.9 lbs 9.5 kg	22.5 lbs 10.2 kg	23.3 lbs 10.6 kg	24.3 lbs 11.0 kg	25.4 lbs 11.5kg
C00	Sri Lanka				

PERFORMANCE PROPERTIES

EN388: 4121						
ABRASION	0	1	2	3	4	-
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-

BARCODES

ITEM	BAG	DOZEN	CASE
■ 56-635/XXL		01616314079770	02616314079779
■ 56-635/XL		01616314079763	02616314079762
■ 56-635/L		01616314079756	02616314079755
■ 56-635/M		01616314079749	02616314079748
■ 56-635/S		01616314079732	02616314079731



DIMENSIONS (in/cm)

	S	M		XL	XXL
A	14.0 / 35.6	14.0 / 35.6	14.0 / 35.6	14.0 / 35.6	14.0 / 35.6
В	4.1 / 10.4	4.3 / 10.8	4.4 / 11.2	4.6 / 11.6	4.7 / 12.0

Thickness: 1.3mm

