

SPECIFICATION SHEET 58-8658K

XTRATUFF™ OIL RESISTANT PVC GLOVE WITH KEVLAR® LINER AND ROUGH GRIP

- Oil resistant, rough coated, sandy coated blue PVC, 13 gauge seamless Kevlar® liner, 12-inch length, cold resistant
- Dupont Kevlar[®] fiber construction provides high tensile strength relative to its weight, is inherently cut resistant and will not melt, ignite or conduct electricity
- Oil and liquid-resistant, staying soft and strong even after exposure to machine oils
- Seamless knit construction protects hands without sacrificing comfort or dexterity
- Straight cuff adds additional length to protect the forearm from liquid run-off
- Rough coated palm provides a great grip
- Seamless Kevlar[®] liner provides cut resistance, excellent tactile sensitivity and is treated to resist germs and odors

APPLICATIONS

- Where machine oil is present
- That require a combination of liquid and cut protection

TECHNICAL DATA

MATERIAL	PVC/Kevlar®			
COLOR	Blue	Blue		
CUFF STYLE	Open Cuff	Open Cuff		
SIZES	M - XL	M - XL		
PACKAGING	12 pairs per dozen, 6	12 pairs per dozen, 6 dozen per case		
CASE	41cm x 44cm x 32ci	41cm x 44cm x 32cm / 16.1" x 17.3" x 12.6"		
CASE WEIGHT	М	L	XL	
	17 kg / 37.5 lbs	17.5 kg / 38.6 lbs	17.8 kg / 39.2 lbs	
C00	China			

PERFORMANCE PROPERTIES

EN388: 4342	ASTM F1790-05 ANSI Cut Level 3					
ABRASION	0	1	2	3	4	-
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-


BARCODES

ITEM	BAG	DOZEN	CASE
58-8658K/M		01616314119360	02616314119369
58-8658K/L		01616314059291	02616314059290
58-8658K/XL		01616314059307	02616314059306



DIMENSIONS (in/cm)

	М		XL
Α	12.0 / 30.5	12.0 / 30.5	12.0 / 30.5
В	4.8 / 12.1	4.9 / 12.5	5.1 / 12.9



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSIY PROVIDED.