



# SPECIFICATION SHEET

## R3V4 KIWI USAR

### PACIFIC R3V4-KIWI USAR™ RESCUE HELMET

- Certified to NFPA 1951; NFPA1971, EN443
- Compliant with ANSI Z89.1
- Lightweight Dupont™ Kevlar® composite shell weighs less than composite fiberglass and composite alternatives
- Shell is not affected by UV exposure
- Composite resins offer higher temperature resistance (up to 600°F) without distorting or melting
- Flip-down eye protector
- Ratchet headband with easy-to-adjust dial which accommodates a variety of head sizes (52-64cm)
- 3-point Nomex® chin strap made from fire resistant Nomex® webbing with quick-release nexus wideguard buckle and postman's slide fastener
- Neck protector (optional) for ear and neck protection
- Full range of tailored Decals/Badges/Reflectorising available
- ESS mounts make goggle attachment quick and easy, even with gloves on
- Face shield protects against hazards and blood borne pathogens (optional)
- NFPA 1971 - must purchase reflectors, neck protector and ESS Innerzone two goggles to meet standard

### APPLICATIONS

- Search and rescue
- Collapse Rescue
- Auto Extrication
- Technical rescue

### TECHNICAL DATA

MATERIAL	Outer Shell: Kevlar® composite / Inner Shell: Polyurethane
SUSPENSION	Pacific mesh ribbon cradle
COLOR	<input type="checkbox"/> Blue (804-3408) <input type="checkbox"/> Daisy (804-3407) <input checked="" type="checkbox"/> Red (804-3406) <input type="checkbox"/> White (804-3405)
SIZES	OSFA, Adjustable
PACKAGING	10 per case
CASE	26.5" x 23.5" x 13" / 67.3cm x 59.7cm x 33.0cm
CASE WEIGHT	25.0 lbs / 11.34 kg
COO	New Zealand

### WARRANTY

6-year limited warranty

Each helmet also carries a 2-year limited warranty on impact liners and ratchet suspensions. Internal parts including crown pads, ribbons and sweatbands are NOT covered by this warranty.

### BARCODES

ITEM	EACH	DOZEN	CASE
<input checked="" type="checkbox"/> 804-3408	616314149283		02616314149281
<input type="checkbox"/> 804-3407	616314149405		02616314149403
<input checked="" type="checkbox"/> 804-3406	616314149597		02616314149595
<input type="checkbox"/> 804-3405	616314149801		02616314149809



### DIMENSIONS (in/cm)

	OSFA			
<b>A</b>	12.2 / 31.0			
<b>B</b>	9.8 / 24.9			
<b>C</b>	6.3 / 16.0			

