

SPECIFICATION SHEET

PACIFIC R3V4-KIWI USAR RESCUE HELMET

- Certified to NFPA 1951; NFPA1971, EN443
- Compliant with ANSI Z89.1
- Lightweight Dupont™ Kevlar® composite shell weighs less than composite fiberglass and composite alternatives
- Shell is not affected by UV exposure
 Composite resins offer higher temperature resistance (up to 600°F) without distorting or melting
- Flip-down eye protector
- Ratchet headband with easy-to-adjust dial which accommodates a variety of head sizes (52-64cm)
- 3-point Nomex[®] chin strap made from fire resistant Nomex[®] webbing with quick-release nexus wideguard buckle and postman's slide fastener
- Neck protector (optional) for ear and neck protection
- Full range of tailored Decals/Badges/Reflectorising available
- ESS mounts make goggle attachment quick and easy, even with gloves on
- Face shield protects against hazards and blood borne pathogens (optional)
- NFPA 1971 must purchase neck protector and ESS Innerzone two goggles to meet standard

APPLICATIONS

- · Search and rescue
- Collapse Rescue
- Auto Extrication
- Technical rescue

TECHNICAL DATA

MATERIAL	Outer Shell: Kevlar® composite / Inner Shell: Polyurethane			
SUSPENSION	Pacific mesh ribbon cradle			
COLOR	Blue (804-3408) Daisy (804-3407) Red (804-3406) White (804-3405)			
SIZES	OSFA, Adjustable			
PACKAGING	10 per case			
CASE	26.5" x 23.5" x 13" / 67.3cm x 59.7cm x 33.0cm			
CASE WEIGHT	25.0 lbs / 11.34 kg			
C00	New Zealand			
HARM CODE	6506.10.6075			

WARRANTY

6-year limited warranty

Each helmet also carries a 2-year limited warranty on impact liners and ratchet suspensions. Internal parts including crown pads, ribbons and sweatbands are NOT covered by this warranty.


BARCODES

ITEM	EACH	DOZEN	CASE
804-3408	616314149283		02616314149281
804-3407	616314149405		02616314149403
804-3406	616314149597		02616314149595
804-3405	616314149801		02616314149809



DIMENSIONS (in/cm)

	OSFA		
Α	12.2 / 31.0		
В	9.8 / 24.9		
С	6.3 / 16.0		



PROTECTIVE INDUSTRIAL PRODUCTS www.pipusa.com • sales@pipusa.com • (800) 262-5755 • (518) 864-0144 fax