

**Models : FP1101W, FP1101WA, FP1101WB, FP1101WC, FP1101WD (single leg)**  
**FP1101DW, FP1101DWA, FP1101DWB, FP1101DWC, FP1101DWD (dual leg)**

## DESCRIPTION



6 feet (1.8 m) single leg or dual leg Web Self-Retracting Lifeline (WSRL).  
 The Type 1 WSRL performs only a locking (fall-stopping) function.  
 These units are for use as part of a complete fall arrest system that must also include a CSA and/or ANSI approved full body harness and a suitable anchorage and/or anchorage connector.  
 Each SRL must be anchored to a suitable structure capable of resisting a static load of 3600 lbs. (16 kN) if certified, or 5000 lbs (22.2 kN) if not certified.  
 This unit is for a single user only.

<b>SIZE</b>	6 ft (1.8 m)	<b>MADE IN</b>	Taiwan
<b>TYPE</b>	Webbing Self-Retracting Lifeline	<b>MATERIALS</b>	1 inch (25 mm) webbing; High Strength Steel Carabiner and Snap
<b>CSA CLASS</b>	CSA Class SRL, ANSI Class B	<b>MAX WORK LOAD</b>	310 lbs (140 kg)
<b>STANDARDS</b>	CSA Z259.2.2-17, ANSI Z359.14-14	<b>MAX ARREST FORCE</b>	8 kN (1800 lbs)
<b>HARDWARE</b>	Certified to CSA Z259.12-16	<b>MAX ARREST DISTANCE</b>	24 in (0.6 m)
<b>COLOR</b>	Black Cover	<b>HARDWARE MIN TENSILE</b>	5000 lbs (22.2 kN)
<b>WEIGHT</b>	2.85 lbs. – 3.75 lbs. (1.3 kg – 1.7 kg)	<b>Temperature Range</b>	-35C to +35C

**Training and Proper Use:** Please refer to product manual included with the products prior to use.

**For Additional Information:** 1-877-446-3278

Revision 1, August 25, 2021

### Head Office

2477, Michelin, Laval, Qc H7L 5B9  
 T: (450) 622-7374/ 1 877 446-3278  
 F: (450) 622-2243/ 1 877 463-2789

### Fall Protection Manufacturing

175B Admiral Blvd., Mississauga, ON L5T 2T3  
 T: (905) 565-9990  
 F: (905) 565-9906