



## Safety Data Sheet

Copyright,2015,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	19-0029-9	<b>Version Number:</b>	2.00
<b>Issue Date:</b>	13/01/2015	<b>Supersedes Date:</b>	30/07/2009

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

### SECTION 1: Identification

#### 1.1. Product identifier

3M(TM) PERFECT-IT(TM) 3000 TRIZACT(TM) SPOT FINISHING MATERIAL PN 6070 , 6071, 6056, 39020

#### Product Identification Numbers

60-9801-0915-5

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive, REMOVAL OF IMPERFECTIONS FROM PAINTED SURFACE

#### 1.3. Supplier's details

**ADDRESS:** 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301  
Petaling, Jaya, Selangor  
**Telephone:** 03-7884 2888  
**E Mail:** 3mmyehsr@mmm.com  
**Website:** www.3M.com.my

#### 1.4. Emergency telephone number

+60 03-7884 2888

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

Not classified as hazardous according to Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

#### 2.2. Label elements

##### Signal word

Not applicable.

##### Symbols

Not applicable.

##### Pictograms

Not applicable.

**2.3. Other hazards**

None known

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	50 - 70
Hydrotreated Light Petroleum Distillates	64742-47-8	10 - 30
ALUMINUM OXIDE	1344-28-1	5 - 15
DECAMETHYLCYCLOPENTASILOXANE	541-02-6	3 - 7
ALUMINUM SILICATE CLAY	66402-68-4	1 - 5
DODECAMETHYLCYCLOHEXASILOXANE	540-97-6	1 - 5
POLOXAMINE	Trade Secret	0.36 1.8
White mineral oil (petroleum)	8042-47-5	< 1

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures**

**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products**

Substance  
Formaldehyde

Condition  
During Combustion

Carbon monoxide  
Carbon dioxide

During Combustion  
During Combustion

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep cool. Store away from acids. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>C.A.S. No.</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional Comments</b>
ALUMINUM OXIDE	1344-28-1	CMRG	TWA:1 fiber/cc	
ALUMINUM OXIDE	1344-28-1	Malaysia OELs	TWA (proposed)(8 hours):10 mg/m3	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
DECAMETHYLCYCLOPENTA SILOXANE	541-02-6	CMRG	TWA:10 ppm	

**3M(TM) PERFECT-IT(TM) 3000 TRIZACT(TM) SPOT FINISHING MATERIAL PN 6070 , 6071, 6056, 39020**

Hydrotreated Light Petroleum Distillates	64742-47-8	CMRG	TWA:165 ppm	
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., Skin Notation
MINERAL OILS, HIGHLY-REFINED OILS	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
OIL MIST, MINERAL	8042-47-5	Malaysia OELs	TWA(as mist)(8 hours):5 mg/m3	
White mineral oil (petroleum)	8042-47-5	CMRG	TWA:5 mg/m3;STEL:10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

**8.2. Exposure controls****8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Neoprene  
Nitrile Rubber

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Physical state**

Liquid

**Specific Physical Form:**

Emulsion

**Appearance/Odor**

Petroleum distillate odor, grey viscous liquid

**Odor threshold***No Data Available*

pH	7.5 - 8.5
Melting point/Freezing point	No Data Available
Boiling point/Initial boiling point/Boiling range	190.6 °C
Flash Point	77.2 °C [Test Method: Closed Cup]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	No Data Available
Vapor Density	No Data Available
Density	0.958 g/ml
Relative Density	0.958 [Ref Std: WATER=1]
Water solubility	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	12 - 16 Pa-s [Test Method: Brookfield]
Volatile Organic Compounds	<= 15 % weight [Test Method: calculated per CARB title 2]
Volatile Organic Compounds	135 g/l [Test Method: calculated SCAQMD rule 443.1]
Percent volatile	80 % weight
VOC Less H2O & Exempt Solvents	366 g/l [Test Method: calculated SCAQMD rule 443.1]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

#### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE > 12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Hydrotreated Light Petroleum Distillates	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrotreated Light Petroleum Distillates	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3.0 mg/l
Hydrotreated Light Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
ALUMINUM OXIDE	Dermal		LD50 estimated to be > 5,000 mg/kg
ALUMINUM OXIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
ALUMINUM OXIDE	Ingestion	Rat	LD50 > 5,000 mg/kg
DECAMETHYLCYCLOPENTASILOXANE	Dermal	Rabbit	LD50 > 15,000 mg/kg
DECAMETHYLCYCLOPENTASILOXANE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 8.7 mg/l
DECAMETHYLCYCLOPENTASILOXANE	Ingestion	Rat	LD50 > 24,134 mg/kg
DODECAMETHYLCYCLOHEXASILOXANE	Dermal	Rat	LD50 > 2,000 mg/kg
DODECAMETHYLCYCLOHEXASILOXANE	Ingestion	Rat	LD50 > 50,000 mg/kg
ALUMINUM SILICATE CLAY	Dermal		LD50 estimated to be > 5,000 mg/kg
ALUMINUM SILICATE CLAY	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
ALUMINUM OXIDE	Rabbit	No significant irritation
DODECAMETHYLCYCLOHEXASILOXANE	Rabbit	No significant irritation
ALUMINUM SILICATE CLAY	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	No significant irritation

**3M(TM) PERFECT-IT(TM) 3000 TRIZACT(TM) SPOT FINISHING MATERIAL PN 6070 , 6071, 6056, 39020**

**Serious Eye Damage/Irritation**

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
ALUMINUM OXIDE	Rabbit	No significant irritation
DODECAMETHYLCYCLOHEXASILOXANE	Rabbit	No significant irritation
ALUMINUM SILICATE CLAY	Rabbit	Mild irritant
White mineral oil (petroleum)	Rabbit	Mild irritant

**Skin Sensitization**

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Guinea pig	Not sensitizing
White mineral oil (petroleum)	Guinea pig	Not sensitizing

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Hydrotreated Light Petroleum Distillates	In Vitro	Not mutagenic
ALUMINUM OXIDE	In Vitro	Not mutagenic
ALUMINUM SILICATE CLAY	In Vitro	Some positive data exist, but the data are not sufficient for classification
White mineral oil (petroleum)	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Hydrotreated Light Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
ALUMINUM OXIDE	Inhalation	Rat	Not carcinogenic
ALUMINUM SILICATE CLAY	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
DODECAMETHYLCYCLOHEXASILOXANE	Ingestion	Not toxic to female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
DODECAMETHYLCYCLOHEXASILOXANE	Ingestion	Not toxic to male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
DODECAMETHYLCYCLOHEXASILOXANE	Ingestion	Not toxic to development	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
White mineral oil (petroleum)	Ingestion	Not toxic to female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not toxic to male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not toxic to development	Rat	NOAEL 4,350 mg/kg/day	during gestation

**3M(TM) PERFECT-IT(TM) 3000 TRIZACT(TM) SPOT FINISHING MATERIAL PN 6070 , 6071, 6056, 39020**

				mg/kg/day	
--	--	--	--	-----------	--

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Hydrotreated Light Petroleum Distillates	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrotreated Light Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ALUMINUM OXIDE	Inhalation	pneumoconiosis   pulmonary fibrosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
DODECAMETHYLCYCLOHEXASILOXANE	Ingestion	endocrine system   liver   respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	28 days
DODECAMETHYLCYCLOHEXASILOXANE	Ingestion	nervous system	All data are negative	Rat	NOAEL 1,000 mg/kg/day	28 days
ALUMINUM SILICATE CLAY	Inhalation	pulmonary fibrosis	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL not available	
ALUMINUM SILICATE CLAY	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL not available	occupational exposure
White mineral oil (petroleum)	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver   immune system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,336 mg/kg/day	90 days

**Aspiration Hazard**

Name	Value
Hydrotreated Light Petroleum Distillates	Aspiration hazard
White mineral oil (petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity**

**Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

**Chronic aquatic hazard:**

Not chronically toxic to aquatic life by GHS criteria.



**3M(TM) PERFECT-IT(TM) 3000 TRIZACT(TM) SPOT FINISHING MATERIAL PN 6070 , 6071, 6056, 39020**

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
ALUMINUM OXIDE	1344-28-1	Water flea	Experimental	48 hours	Effect Concentration 50%	>100 mg/l
ALUMINUM OXIDE	1344-28-1	Green algae	Experimental	72 hours	Effect Concentration 50%	>100 mg/l
ALUMINUM OXIDE	1344-28-1	Fish	Experimental	96 hours	Lethal Concentration 50%	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Bluegill	Experimental	96 hours	Lethal Level 50%	>100 mg/l
ALUMINUM OXIDE	1344-28-1	Green algae	Experimental	72 hours	No obs Effect Conc	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Experimental	21 days	No obs Effect Conc	>100 mg/l
ALUMINUM SILICATE CLAY	66402-68-4		Data not available or insufficient for classification			
DECAMETHYLCYCLOPENTASILOXANE	541-02-6		Data not available or insufficient for classification			
DODECAMETHYLCYCLOHEXASILOXANE	540-97-6		Data not available or insufficient for classification			
Hydrotreated Light Petroleum Distillates	64742-47-8		Data not available or insufficient for classification			

**12.2. Persistence and degradability**

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
DECAMETHYLCYCLOPENTASILOXANE	541-02-6	Experimental Photolysis		Photolytic half-life (in air)	20.4 days (t 1/2)	Other methods
ALUMINUM SILICATE CLAY	66402-68-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrotreated Light Petroleum Distillates	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Water	7732-18-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**3M(TM) PERFECT-IT(TM) 3000 TRIZACT(TM) SPOT FINISHING MATERIAL PN 6070 , 6071, 6056, 39020**

ALUMINUM OXIDE	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
DECAMETHYLCYCLOPENTASILOXANE	541-02-6	Experimental Biodegradation	28 days	Percent degraded	0.14 % weight	Other methods
DODECAMETHYLCYCLOHEXASILOXANE	540-97-6	Experimental Biodegradation	28 days	Carbon dioxide evolution	4.46 % weight	Other methods
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	Carbon dioxide evolution	0 % weight	OECD 301B - Mod. Sturm or CO2

**12.3. Bioaccumulative potential**

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrotreated Light Petroleum Distillates	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Water	7732-18-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
ALUMINUM OXIDE	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
DECAMETHYLCYCLOPENTASILOXANE	541-02-6	Experimental BCF - Fathead Mi	105 days	Bioaccumulation Factor	13300	Other methods
DODECAMETHYLCYCLOHEXASILOXANE	540-97-6	Experimental BCF - Fathead Mi	49 days	Bioaccumulation Factor	1160	OECD 305E-Bioaccum FI-thru fis
ALUMINUM SILICATE CLAY	66402-68-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available

**SECTION 13: Disposal considerations**

### 13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

## SECTION 14: Transport Information

### Marine Transport (IMDG)

**UN Number:** None assigned.  
**Proper Shipping Name:** None assigned.  
**Technical Name:** None assigned.  
**Hazard Class/Division:** None assigned.  
**Subsidiary Risk:** None assigned.  
**Packing Group:** None assigned.  
**Limited Quantity:** None assigned.  
**Marine Pollutant:** None assigned.  
**Marine Pollutant Technical Name:** None assigned.  
**Other Dangerous Goods Descriptions:**  
None assigned.

### Air Transport (IATA)

**UN Number:** None assigned.  
**Proper Shipping Name:** None assigned.  
**Technical Name:** None assigned.  
**Hazard Class/Division:** None assigned.  
**Subsidiary Risk:** None assigned.  
**Packing Group:** None assigned.  
**Limited Quantity:** None assigned.  
**Marine Pollutant:** None assigned.  
**Marine Pollutant Technical Name:** None assigned.  
**Other Dangerous Goods Descriptions:**  
None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS. Contact 3M for more information. The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply.

Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA.

## **SECTION 16: Other information**

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**3M Malaysia SDSs are available at [www.3M.com.my](http://www.3M.com.my)**