

MINI ZTEK®

BETTER SUITED FOR SMALLER FACIAL FEATURES



PART	LENS
S2510SN***	<input type="checkbox"/> Clear
S2510SNT***	<input type="checkbox"/> Clear (Anti-Fog)
S2517SN***	<input type="checkbox"/> Pink
S2520SN***	<input type="checkbox"/> Gray
S2530SN***	<input type="checkbox"/> Amber
S2560SN**	<input type="checkbox"/> Infinity Blue
S2575SN***	<input type="checkbox"/> Blue Mirror
S2580SN***	<input type="checkbox"/> Indoor/Outdoor Mirror

- Mini Ztek has all the great features of the ZTEK in a design better suited for smaller facial features.
- Integrated nose piece.
- Soft, non-slip rubber temple tips provide non-binding fit.
- Economical wrap-around single lens provides full panoramic view.
- Lenses are coated for superior scratch resistance, provides 99.9% protection from harmful UV rays.

GENERAL SPECIFICATION
Bridge: 12mm
Lens Base: 10 Curve
Lens Size Diagonal: 73.8mm
Lens Size Vertical: 41mm
Lens Thickness: 2.3mm
Overall Length (Lens-Tip): 144mm
Overall Width (Hinge-Hinge): 128mm
PD: 50mm
Weight: 20gm
Closest point between lens: 15.2mm
Closest point between temple tips: 83mm

MINI ZTEK®

BETTER SUITED FOR SMALLER FACIAL FEATURES









PACKAGING

Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Attractive & stylish unitary lens
Frame	Polycarbonate	Matted finish integral to lens
Side Shield	Polycarbonate	Integral to lens
Nose Piece	Polycarbonate	V bridge - integral to lens
Temple	Polycarbonate	Matte finish - straight back design
Temple Tips	PVC	Soft to prevent slippage
Hinge	Polycarbonate	3 barrel type, integral to frame
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
S2510SNT	 Clear	P Z87 + H U6	P Z87 + H / P c SEI CAN/CSA Z94.3-07
S2510SNT	 Clear (Anti-Fog)	P Z87 + H U6	P Z87 + H / P c SEI CAN/CSA Z94.3-07
S2517SN	 Pink	P Z87 + H	P Z87 + H / P c SEI CAN/CSA Z94.3-07
S2520SN	 Gray	P Z87 + H U6 L2.5	P Z87 + H / P c SEI CAN/CSA Z94.3-07
S2530SN	 Amber	P Z87 + H U6	P Z87 + H / P c SEI CAN/CSA Z94.3-07
S2560SN	 Infinity Blue	P Z87 + H U6 L1.3	P Z87 + H / P c SEI CAN/CSA Z94.3-07
S2575SN	 Blue Mirror	P Z87 + H S	P Z87 + H / P c SEI CAN/CSA Z94.3-07
S2580SN	 Indoor/Outdoor Mirror	P Z87 + H U6 L1.7	P Z87 + H / P c SEI CAN/CSA Z94.3-07

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

W: Welding Filter

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices