



PYRAMEX
Perform At Your Peak



Intruder® ANSI CE CSA



Integrated nosepiece

Lightweight frameless protection

Foam padding is available in select options

Part No.	Lens and Temples
S4110S ●●●	Clear
PYS4110S* ●●	Clear
S4110ST ●●●	AF Clear
S4110SUC ●	Uncoated Clear
S4120S ●●●	Gray
PYS4120S* ●●	Gray
S4120ST ●●●	AF Gray
S4130S ●●●	Amber
PYS4130S* ●●	Amber
S4160S ●●	Infinity Blue
S4170S ●●	Silver Mirror
S4175S ●	Blue Mirror
S4180S ●●	I/O Mirror
S4180ST ●	AF I/O Mirror
Part No.	Foam Padded Frame
S4110STFP ●	AF Clear
S4120STFP ●	AF Gray
S4180STFP ●	AF I/O Mirror
Part No.	Black Temples
SB4110S ●●	Clear
Part No.	Blue Temples
SN4110S ●●	Clear
Part No.	Red Temples
SR4110S ●●	Clear

*Pyramex retail packaged product



There's more to see at
PYRAMEXSAFETY.COM
(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●) or Canadian (CSA Z94.3) (●).



PYRAMEX
Perform At Your Peak



Intruder and Mini Intruder Multi-Colors **ANSI CE CSA**

Sold in dozen quantity only

Comes with six assorted temple colors: red, blue, green, purple, orange and black

Multi-pack includes two of each temple color with clear lenses

Perfect for work areas where color coding is necessary

Part No.	Multi-Color Temples
S4110SMP ●●●	Clear [Intruder]
S4110SNMP ●	Clear [Mini Intruder]



Mini Intruder **ANSI**

Mini Intruder has all the great features of Intruder in a design better suited for smaller facial size

Part No.	Lens and Temples
S4110SN ●	Clear
S4110SNT ●	AF Clear
S4120SN ●	Gray
S4130SN ●	Amber
S4180SN ●	I/O Mirror



Intruder® Readers **ANSI**

Integrated nosepiece

Lightweight frameless protection

Part No.	Lens and Temples
S4110R15 ●	Clear +1.5 Mag
S4110R20 ●	Clear +2.0 Mag
S4110R25 ●	Clear +2.5 Mag

There's more to see at
PYRAMEXSAFETY.COM
(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards [●] and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European [EN166] [●] or Canadian [CSA Z94.3] [●].

Intruder®

General Specifications

Weight: 23.1 gm
 PD: 64 mm
 Bridge: 17.27 mm
 Lens base: 10 curve
 Lens size diagonal: 77.08 mm
 Lens size vertical: 43.38 mm
 Lens thickness: 2.5 mm
 Overall length (lens - tip): 156 mm
 Overall width (hinge - hinge): 135.5 mm
 Closest point between temples: 91.53 mm
 Closest point between lens: 16.67 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: polycarbonate
 Screw: stainless steel

Part No.	Lens Markings	Frame Markings
S4110S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
PYS4110S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
S4110ST	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
S4110SUC	P Z87 + U6	P Z87 +
S4120S	P Z87 + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-15
PYS4120S	P Z87 + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-15
S4120ST	P Z87 + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-15
S4130S	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
PYS4130S	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
S4160S	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
S4170S	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
S4175S	P Z87 + S	P Z87 +
S4180S	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
S4180ST	P Z87 + U6 L1.7	P Z87 +
S4110STFP	P Z87 + U6	P Z87 +
S4120STFP	P Z87 + U6 L3	P Z87 +
S4180STFP	P Z87 + U6 L1.7	P Z87 +
SB4110S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SN4110S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SR4110S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
S4110SMP	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special purpose
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L3: 18% max visible light

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

Mini Intruder

General Specifications

Weight: 17.9 gm
 PD: 62 mm
 Bridge: 14.17 mm
 Lens base: 11 curve
 Lens size diagonal: 69.43 mm
 Lens size vertical: 39.92 mm
 Lens thickness: 2.1 mm
 Overall length (lens - tip): 144 mm
 Overall width (hinge - hinge): 121.8 mm
 Closest point between temples: 77.83 mm
 Closest point between lens: 14.38 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: polycarbonate
 Screw: stainless steel

Part No.	Lens Markings	Frame Markings
S4110SN	P Z87 + H U6	P Z87 +
S4110SNT	P Z87 + H U6	P Z87 +
S4120SN	P Z87 + H U6 L3	P Z87 +
S4130SN	P Z87 + H S	P Z87 +
S4180SN	P Z87 + H U6 L1.7	P Z87 +
S4110SNMP	P Z87 + H U6	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 H: Small head size
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L3: 18% max visible light

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact





Intruder® Readers

General Specifications

Weight: 23.1 gm
 PD: 64 mm
 Bridge: 17.27 mm
 Lens base: 10 curve
 Lens size diagonal: 77.08 mm
 Lens size vertical: 43.38 mm
 Lens thickness: 2.5 mm
 Overall length (lens - tip): 156 mm
 Overall width (hinge - hinge): 135.5 mm
 Closest point between temples: 91.53 mm
 Closest point between lens: 16.67 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: polycarbonate
 Screw: stainless steel

Part No.	Lens Markings	Frame Markings
S4110R15	P Z87 + U6	+1.5 P Z87 +
S4110R20	P Z87 + U6	+2.0 P Z87 +
S4110R25	P Z87 + U6	+2.5 P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Frame Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5
 P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 - 2: Rx
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967