





GRAVEX®



PART	LENS
SB8910S••	 Clear
SB8910ST•••	 Clear H2X Anti-Fog
SB8920S••	 Gray
SB8980S••	 Indoor/Outdoor Mirror

- Built-in nose piece secures the glass and prevents slipping.
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection.
- 9.75 base curve lens provides full side protection without distracting seams or traditional type side shields.

GENERAL SPECIFICATION

Bridge: 10.06mm
Lens Base: 9.5 Curve
Lens Size Diagonal: 80mm
Lens Size Vertical: 46.5mm
Lens Thickness: 2.3mm
Overall Length (Lens-Tip): 156mm
Overall Width (Hinge-Hinge): 138.2mm
PD: 68mm
Weight: 25gm
Closest point between lens: 14.1mm
Closest point between temple tips: 72mm





PACKAGING

Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	9.5 base curve with close-fitting protection
Frame	Nylon	Semi-frame style, slim and lightweight
Temples	Nylon	Engraved grids on tips for better grip
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB8910S	 Clear	P Z87 + U6	P Z87 + P c SEI CAN/CSA Z94.3-07
SB8910ST	 Clear H2X Anti-Fog	P Z87 + U6	P Z87 + P c SEI CAN/CSA Z94.3-07
SB8920S	 Gray	P Z87 + U6 L2.5	P Z87 + P c SEI CAN/CSA Z94.3-07
SB8980S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 + P c SEI CAN/CSA Z94.3-07

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

W: Welding Filter

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices