

ALKYD

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®
INDUSTRIAL
— CHOICE —**TECHNICAL DATA****IC-05****AF1600 SYSTEM
ATHLETIC FIELD STRIPING PAINT AEROSOL****DESCRIPTION AND USES**

A fast dry, water-based inverted aerosol striping paint, designed specifically for striping athletic fields. It dries fast in 30 minutes and creates sharp, well defined lines. It is safe for use on grass, smudge resistant, durable and long-lasting.

PRODUCTS

SKU	Description
206043	White
206045	Yellow
206044	Orange
257403	Fluorescent Green
257406	Fluorescent Orange

PACKAGING

20 fl. oz. aerosol container (17 oz. weight fill)
12 aerosols/carton

PRODUCT APPLICATION**APPLICATION**

Use when temperature is above 32°F (0°C) and humidity is below 85% to ensure proper drying. Do not apply over dew or wet ground. Protect surrounding surfaces from overspray. Overspray can carry a significant distance.

PRODUCT APPLICATION (cont.)

The Athletic Field Striping sprays are designed for use with the Rust-Oleum Athletic Field Striping Machine item #206346. The Athletic Field Striping Machine has larger diameter wheels to accommodate high grass conditions. Follow machine directions for proper use.

The width of the stripe can be varied from 3 to 6 inches wide by adjusting the position of the can holder on the Striping Machine.

For best results be sure the Striping Machine is in motion before squeezing the trigger and release the trigger before stopping.

The athletic field striping aerosols can also be used with the #2388000 Striping Wand.

Clean valve by spraying upright for 2 to 3 seconds after each use. If valve clogs, carefully remove spray tip and clean in thinner. **Do not** insert any object into the can opening.

PHYSICAL PROPERTIES

		ATHLETIC FIELD STRIPING PAINT
Resin Type		Modified Alkyd
Pigment Type		Varies with color
Solvents		Acetone, Toluene, VM&P Naphtha, Water, Xylene
MIR		Maximum value of 1.0
Fill Weight		17 oz.
Practical Coverage		Approximately 100-200 linear feet at 3" wide (30-60 m. at 7.6 cm.)
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Tack-Free	<30 minutes
	Full use	30 minutes
Shelf Life		5 years
Safety Information		For additional safety information, see SDS

Calculated values are shown and may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM
INDUSTRIAL BRANDSRust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM CompanyPhone: 877-385-8155
www.rustoleum.com/industrialForm: GDH-596
Rev.: 010517