

# **SAFETY DATA SHEET**

**Issuing Date** No data available **Revision Date** 11-May-2015 **Revision Number:**0

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

**GHS** product identifier

**Product Name** Rustlick 606 Aerosol

Other means of identification

**Synonyms** None

Recommended use of the chemical and restrictions on use

Recommended Use Moisture-absorbing rust preventative

Uses advised against No information available

Manufacturer

Manufacturer Name/Address/Phone Number

**ITW Pro Brands** 

616 East Industrial Street

DeWitt, IA 52742

TEL: 1-800-241-8334 for US/ +1 770-243-8800 outside US

**Emergency telephone number** 

**Emergency Telephone** 

Number CHEMTREC: 1-800-424-9300 for US/ 703-527-3887 outside US

#### 2. HAZARDS IDENTIFICATION

#### Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Aspiration Hazard	Category 1	
Flammable Aerosols	Category 1	
Gases Under Pressure	Liquefied Gas	

### GHS Label elements, including precautionary statements

### **Emergency Overview**

#### Signal Word Danger

#### **Hazard Statements**

- May be fatal if swallowed and enters airways
- Extremely flammable aerosol
- Contains gas under pressure; may explode if heated







Appearance: Red Brown

Physical State: Liquid

Odor: Mild



### **Precautionary Statements**

#### Prevention

- Keep away from heat/sparks/open flames/hot surfaces No smoking.
- Do not spray on an open flame or other ignition source
- Pressurized container: Do not pierce or burn, even after use.

#### **General Advice**

None

#### Ingestion

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- · Do NOT induce vomiting.

### Storage

- Store locked up.
- Store in a well-ventilated place.
- Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F

#### Disposal

Dispose of contents/container to an approved waste disposal plant.

### **Hazard Not Otherwise Classified (HNOC)**

Not applicable

#### Other information

No information available.

7% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION / INFORMATION ON INGREDIENTS					
Chemical Name	CAS-No	Weight%	Trade Secret		
Petroleum distillates, hydrotreated light	64742-47-8	30-60	*		
Propane	74-98-6	7-13	*		
Butane	106-97-8	5-10	*		
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	5-10	*		
Sodium dodecylbenzenesulfonate	25155-30-0	1-5	*		

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of necessary first-aid measures** 

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. Get medical attention if irritation persists.

**Skin Contact** Wash skin with soap and water. Get medical advice/attention if irritation

persists.



Rustlick 606 Aerosol Revision Date: 11-May-2015

**Inhalation** If experiencing respiratory symptoms: Call a POISON CENTER or

doctor/physician.

Ingestion IF SWALLOWED: Call a POISON CENTER or doctor/ physician

immediately. DO NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

Indication of immediate medical attention and special treatment needed, if necessary

**Notes to Physician** Treat symptomatically. Aspiration hazard.

### 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use: Water spray, Carbon dioxide (CO 2), Foam, Dry chemical.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread

fire.

**Specific Hazards Arising from the Chemical** 

Flammable. Containers may explode when heated. Cool containers/tanks with water spray Pressurized container: Do not pierce or burn, even after use.

**Explosion Data** 

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge Yes.

**Protective Equipment and Precautions for Firefighters** 

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Evacuate personnel to safe areas. Keep people away from and

upwind of spill/leak. Do not puncture or incinerate cans.

**Environmental Precautions** 

**Environmental Precautions** Prevent entry into waterways, sewers, basements or confined

areas. Do not flush into surface water or sanitary sewer system.

See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

**Methods for Containment** A vapor suppressing foam may be used to reduce vapors.

Methods for Cleaning Up Soak up with inert absorbent material (e.g. sand, silica gel, acid

binder, universal binder, sawdust). Use clean non-sparking tools to collect absorbed material. Sweep up and shovel into suitable

containers for disposal.

#### 7. HANDLING AND STORAGE



Rustlick 606 Aerosol Revision Date: 11-May-2015

Precautions for safe handling

**Handling** Keep away from heat, sparks and open flame. No smoking. Do

not spray on an open flame or other ignition source. Pressurized

container: Do not pierce or burn, even after use.

Conditions for safe storage, including any incompatibilities

Storage Protect from sunlight. Do not expose to temperatures exceeding

50°C/ 122°F.

**Incompatible Products** Strong oxidizing agents.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Control parameters**

### **Exposure Guidelines**

Chemical Name ACGIH TLV		OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated light 64742-47-8	treated light STEL: 10 mg/m3   TWA: 5 mg/m3 (as oil mist)		-
Propane 74-98-6	' I IWA: 1000 nnm I '.		IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³
Butane 106-97-8	- 1000 nnm		TWA: 800 ppm TWA: 1900 mg/m³
Hexylene glycol 107-41-5 Ceiling: 25 ppm		(vacated) Ceiling: 25 ppm (vacated) Ceiling: 125 mg/m³	Ceiling: 25 ppm Ceiling: 125 mg/m³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

### Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

#### Individual protection measures, such as personal protective equipment

**Eye/Face Protection**Safety glasses with side-shields.

Skin and Body Protection
Protective gloves.

**Respiratory Protection** I If exposure limits are exceeded or irritation is experienced,

NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.



### **Hygiene Measures**

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

None known

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

**Physical State** Aerosol Red Brown **Appearance** 

Odor **Odor Threshold** mild No information available

Remarks/ - Method **Property** Values

No data available Ph None known Melting Point/Range No data available None known **Boiling Point/Boiling Range** No data available None known **Flash Point** -104 °C / -156 °F **PMCC Evaporation rate** >1 None known

Flammability (solid, gas)

No data available

Flammability Limits in Air

upper flammability limit 8.4 lower flammability limit 1.8

**Vapor Pressure** No data available

**Vapor Density** >1 None known **Specific Gravity** 0.86 None known Insoluble in water. **Water Solubility** None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/water No data available None known **Autoignition Temperature** No data available None known **Decomposition Temperature** No data available None known No data available Viscosity None known

Viscosity, kinematic <20.5 cPs

Flammable Flammable Properties

**Explosive Properties** No data available Oxidizing Properties No data available

Other information

**VOC Content (%)** 72%

### 10. STABILITY AND REACTIVITY

#### Reactivity

No data available.

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

#### **Hazardous Polymerization**

Hazardous polymerization does not occur.



Rustlick 606 Aerosol Revision Date: 11-May-2015

#### Conditions to avoid

Heat, flames, sparks. Protect from temperatures above 50°C/ 122°F.

### **Incompatible materials**

Strong oxidizing agents.

### **Hazardous decomposition products**

Carbon oxides, Hydrocarbons.

### 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on

known or supplied information.

InhalationThere is no data available for this productEye ContactThere is no data available for this product

**Skin Contact** Prolonged skin contact may defat the skin and produce

dermatitis.

**Ingestion** May be fatal if swallowed and enters airways.

**Component Information** 

Chemical Name			LC50 Inhalation	
Petroleum distallates, hydrotreated light			> 5.2 mg/L (Rat) 4 h	
Propane -		-	= 658 mg/L (Rat) 4 h	
Butane	Sodium = 483 mg/kg ( Rat )		= 658 mg/L (Rat) 4 h	
Sodium dodecylbenzenesulfonate			-	

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Difficulty in breathing.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

SensitizationNo information available.Mutagenic EffectsNo information available.

Carcinogenicity Petroleum products are known to cause cancer because of

carcinogenic components (e.g. benzene, DMSO). These carcinogenic components are typically found in crude petroleum products and are removed through the refinement process.

ACGIH: (American Conference of Governmental Industrial Hygienists)

None

IARC: (International Agency for Research on Cancer)

None

**OSHA: (Occupational Safety & Health Administration)** 

X - Present



### Rustlick 606 Aerosol

Reproductive Toxicity

STOT - single exposure

STOT - repeated exposure

No information available.

No information available.

No information available.

**Aspiration Hazard** May be fatal if swallowed and enters airways.

**Numerical measures of toxicity - Product** 

**Acute Toxicity** 7% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 7480 mg/kg; Acute toxicity estimate

#### 12. ECOLOGICAL INFORMATION

Revision Date: 11-May-2015

### **Ecotoxicity**

Not classified.

<7 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum distillates, hydrotreated heavy naphthenic 64742-47-8		LC50 96 h: = 45 mg/L flow-through (Pimephales promelas) LC50 96 h: = 2.2 mg/L static (Lepomis macrochirus) LC50 96 h: = 2.4 mg/L static (Oncorhynchus mykiss)		LC50 96 h: = 4720 mg/L (Den-dronereides heteropoda)
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5		LC50 96 h: > 5000 mg/L (Oncorhynchus mykiss)		EC50 48 h: > 1000 mg/L (Daphnia magna)
Sodium dodecylbenzenesulfonate 25155-30-0		LC50 96 h: = 10.8 mg/L static (Oncorhynchus mykiss)		

Persistence and Degradability Bioaccumulation

No information available. No information available.

Chemical Name	Log Pow
Propane	2.3
Butane	2.89

#### Other Adverse Effects

No information available.



13. DISPOSAL CONSIDERATIONS

**Waste Disposal Methods** This material, as supplied, is a hazardous waste according to

Federal regulations (40CFR 261).

**Contaminated Packaging** Empty containers pose a potential fire and explosion hazard. Do not cut,

puncture or weld containers. Do not re-use empty containers.

**US EPA Waste Number** D001

14. TRANSPORT INFORMATION

DOT

**UN-Number** Consumer commodity

Proper shipping name ORM-D

**Hazard Class** Consumer commodity, ORM-D

**Emergency Response Guide** 126

Number

**TDG** 

**UN-Number** UN1950 Proper shipping name Aerosols **Hazard Class** 2.1

Description UN1950, Aerosols, 2.1, Limited Quantity

MEX

**UN-Number** UN1950 Proper shipping name Aerosols **Hazard Class** 

Description UN1950, Aerosols, 2.1, Limited Quantity

**ICAO** 

**UN-Number** UN1950 Proper shipping name Aerosols **Hazard Class** 2.1

Description UN1950, Aerosols, 2.1

IATA

**UN-Number** UN1950

Aerosols, flammable Proper shipping name

**Hazard Class** 2.1 **ERG Code** 10L

**Description** UN1950, Aerosols, 2.1, Limited Quantity

IMDG/IMO

**UN-Number** UN1950 Proper shipping name Aerosols **Hazard Class** 2

See SP63 **Subsidiary Class** EmS No. F-D, S-U

Description UN1950, Aerosols, 2.1, (See SP63), (-104°C c.c.), Limited Quantity



**RID** 

**UN-Number** UN1950 **Proper shipping name** Aerosols

Hazard Class 2 Classification Code 5F

**Description** UN1950, Aerosols, 2.1, Limited Quantity

<u>ADR</u>

UN-Number UN1950
Proper shipping name Aerosols
Hazard Class 2

Classification Code 5F Tunnel Restriction Code (D)

**Description** UN1950, Aerosols, 2.1, (D), Limited Quantity

<u>ADN</u>

Proper shipping name Aerosols
Hazard Class
Classification Code 5F

**Special Provisions** 190,327,344, 625

**Description** UN1950, Aerosols, 2.1, (D), Limited Quantity

Limited Quantity 1 L

Ventilation VE01, VE04

#### 15. REGULATORY INFORMATION

**International Inventories** 

TSCA Complies DSL Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

### **U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard
Chronic Health Hazard
Fire Hazard
Sudden Release of Pressure Hazard
Reactive Hazard
No



### **Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sodium dodecylbenzenesulfonate	1000 lb			X

### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Sodium	1000 lb		RQ 1000 lb final RQ
dodecylbenzenesulfonate	1000 lb		RQ 454 kg final RQ

### **U.S. State Regulations**

### **California Proposition 65**

This product does not contain any Proposition 65 chemicals.

### **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Propane	X	X	X	-	Х
Butane	×	Х	X		Х
Petroleum distillates, hydrotreated heavy naphthenic				Х	
Sodium dodecylbenzenesulfonate	Х	X	×		

## **U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable



### **16. OTHER INFORMATION**

NFPA Health Hazard 1 Flammability 3 Instability 0 Physical and

Chemical Hazards -

HMIS Health Hazard 1 Flammability 3 Physical Hazard 0 Personal Protection X

\*Indicates a chronic health hazard.

### **Prepared By**

ITW Pro Brands 616 East Industrial Street DeWitt. IA 52742

TEL: 1-800-241-8334 for US/ +1 770-243-8800 outside US

Revision Date 11-May-2015

Revision Note No information available.

### **General Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet** 

