


SPECIFICATION SHEET

HD-INSERT

Re-Enforce Heavy Duty Insert

- Designed to fit into the underside of existing Safe-Flex™ tiles to create the ability to handle heavy duty loads.
- Suitable for areas with heavy machines or skids, or aisleways made for heavy equipment traffic.
- Sold in sets of four.
- Inserts have doubled sided tape already applied for easy installation.*



| DIMENSIONS | 0.7" x 15.8" x 15.8" | | |
|------------------|--|--|--|
| WEIGHT | 4.8 lbs | | |
| COMPOSITION | 100% Recycled PVC | | |
| DUROMETER | 95A | | |
| SPECIFIC GRAVITY | 1.36 | | |
| FLAMMABILITY | 0.61 watts/cm2 -Class 1 fire resistant | | |
| COLOR | Black | | |

^{*}For an additional charge, product can arrive to you already installed into new tiles. Speak to your representative for more information and conditions.

LOADING CHART

| OBJECT | FORK TRUCK | PUMP CART | DOLLY | CART W/ LARGE CASTERS | CART W SMALL CASTERS |
|----------------|------------|--------------|-------|--------------------------|-------------------------|
| MAX LOAD (LBS) | 10,000 | 2,000 | 2,000 | 3,000 | 1,500 |
| MAX LOAD (KG) | 4,535 | 907 | 907 | 1,361 | 680 |

NOTE: Total load across 4 contact points. These max loads are for reference only.

