


## Support pads for CoroDrill® 800 solid drill heads

### Support pad PM1



### Support pad P1 and M1



Ordering code	Dimensions, mm, inch															
	P		M		K		N		S							
	GC	GC	GC	GC	GC	GC	GC	GC	GC	GC						
	P1	PM1	M1	PM1	M1	PM1	M1	PM1	M1	PM1						
	W1	W1"	INSL	INSL"	S	S"										
800-06A	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆	6	.236	18	.709	3.0	.118
800-07A	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆	7	.276	20	.787	3.5	.138
800-08A	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆	8	.315	25	.984	4.5	.177
800-10A	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆	10	.394	30	1.181	4.5	.177
800-12A	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆	12	.472	35	1.378	5.5	.216

For more information on geometries and grades, see page 36

Ordering example: 10 pieces 800-06A P1

Support pad	Shim set (8 pcs)	S
800-06A	5549 127-85	0.02
	5549 127-86	0.03
800-07A	5549 127-88	0.02
	5549 127-89	0.03
800-08A	5549 127-91	0.02
	5549 127-92	0.03
800-10A	5549 127-94	0.02
	5549 127-95	0.03
800-12A	5549 127-97	0.02
	5549 127-98	0.03

Note: Do not add more than 0.05 mm thickness of shims