



Okuma Multus U3000, 4000 2S

Toolholder Program




Multus U3000, 4000 2S

Coromant Capto® Program




OD clamping unit

C4	C4-TRE-OK60A (343-830111C375-RC)	Standard
C4	C4-TLE-OK60A (343-830111C375-LC)	Standard




OD clamping unit, short

C4	343-830111C447	For quotation
----	----------------	---------------




OD clamping unit, both sides

C4	C4-TRE-OK60A-DT (343-830111C376-RC)	Standard
C4	C4-TLE-OK60A-DT (343-830111C376-LC)	Standard




Face and ID clamping unit

C4	C4-TRI-OK60C (343-830111C1074-RC)	Standard
C4	C4-TLI-OK60C (343-830111C1074-LC)	Standard




Face and ID clamping unit, both sides

C4	C4-TRI-OK60C-DT (343-830111C1075-RC)	Standard
C4	C4-TLI-OK60C-DT (343-830111C1075-LC)	Standard



Cut-off holder, adjustable

SH 32	APB-TNE-OK60A-25	Standard
-------	------------------	----------



Cut-off holder, adjustable, IC

HF=25	APBR-OK60A-25-HP IC 80 (343-810100R7) bar	Standard
HF=25	APBL-OK60A-25-HP IC 80 (343-810100L7) bar	Standard


Multus U3000, 4000 2S

Coromant Capto® Program




Cut-off holder, adjustable, long, IC

HF=25	343-810100R48 (48-101968R)	IC 80 bar	For quotation
HF=25	343-810100L48 (48-101968L)	IC 80 bar	For quotation




OD drill/milling unit

C4	C4-DNE-OK60A-E (410104045-60)	1:1	EC	Standard
C4	C4-DNE-OK60A-I (410104046-60)	1:1	IC 80 bar	Standard




OD drill/milling unit (special offer!)

C4	343-830820N1770 (410104039-60)	1:1	EC	For quotation
----	-----------------------------------	-----	----	---------------



Face drill/milling unit

C4	343-830820N2613 (410504075-60)	1:1	EC	For quotation
C4	343-830820N2614 (410504076-60)	1:1	IC 80 bar	For quotation



Face drill/milling unit, both sides

C4	343-830820N2615 (410504077-60)	1:1	EC	For quotation
----	-----------------------------------	-----	----	---------------