

Scotch®

Clean Removal Strapping Tape

8899HP

Technical Data Sheet

June 2016

Product Description Scotch® Clean Removal Strapping Tape 8899HP is a high-performance tape with a tensilized polypropylene film backing and pressure-sensitive adhesive. The backing provides proper stiffness for manual or semi-automatic dispensing of short to long lengths of tape. The pressure-sensitive adhesive is specifically formulated to provide balanced adhesion, clean removal, and stain resistance on surfaces such as painted metals, plastic, and glass. It is recommended that appropriate tests be conducted on the specific surfaces the tape will be adhered to in order to determine the strapping tape's suitability for the intended application.

Product Construction	Backing	Adhesive	Backing Color
	Tensilized Polypropylene	High Performance Pressure-Sensitive Rubber	Blue, White, Ivory

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	55 oz./in. width (60 N/100 mm width)	D-3330
Tensile Strength:	170 lbs./in. width (2977 N/100 mm width)	D-3759
Elongation at Break:	30 %	D-3759
Total Thickness:	4.8 mil (0.122 mm)	D-3652

Features

- The pressure-sensitive adhesive is specifically formulated to provide balanced adhesion, clean removal, and stain resistance on surfaces such as painted metals, plastic, and glass.
- The balanced product construction is easy to dispense with an H-10 hand dispenser and the M-82 Definite length dispenser.

Application Ideas

- The tape is designed to secure painted metals, metal, plastic, and glass parts and components in place during manufacture and shipment across a variety of industries including appliance, electronic, metal working and packaging.
- Securing: trays, racks, doors, glass plates, holding shelves, and power cords in place during shipping.
- Attachment of small parts, poly bag information sheets, foam and corrugated board.
- Light weight coil tabbing, splicing, bundling and wrapping.

Scotch® Clean Removal Strapping Tape

8899HP

Storage Conditions

Store behind present stock. Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40-50% relative humidity are recommended. Rotate your stock

Shelf Life

To obtain best performance, use this product within 18 months from date of manufacture.

Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M

Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (Fax)
www.3M.com/iatd



Recycled Paper
40% pre-consumer
10% post-consumer

Scotch is a registered trademark of 3M.
Printed in U.S.A.
©3M 2016 (6/16)