

## 3M<sup>™</sup> CF-DC – Clean and Finishing Disc



## **Product Construction**

Mineral and Grit

Size

Tipo A : coarse, medium, fine, very fine

Diameter	Holes	
150 mm	8 mm / 20 mm	
180 mm	8 mm / 20 mm	
200 mm	20 mm	
250 mm	20 mm	
300 mm	20 mm / 30 mm	

Available Forms		
	f	
Applications		
Materials: Metal, wood and plastic		
ı f	f	
Recommendation		

For cleaning light blemishes; secondary treatment of brushed areas; i.e, surface repairs, repainting, intermediate lacquer sanding and preparation prior to glueing or painting final coats.



## 3M<sup>™</sup> CF-DC – Clean and Finishing

Features		Advantages		Benefits
Three-dimensional Scoth-Brite <sup>™</sup> web	$\sum$	Uniform grain dispersion; conformable to workpiece contours		Consistent, repeatable finish results; won't change the geometry of the workpiece
Nylon non-woven web		Free of corrosion-inducing materials		Metal pure surfaces
	$\sum$		$\sum$	
CF Material with Aluminium oxide mineral (Type A)		Tough abrasive grain		Fine, matt scratch pattern
	$\sum$		$\sum$	,
CF Material with Silicon carbide mineral (Type S)	$\sum$	Hard, sharp grain	$\sum$	Striking scratch pattern with a finer structure
F Material		Softer abrasive grain	_	Special finish; polish effect via grinding paste
Machines		Safety		
		Quality		
		3M Plants are	ISO 90	02 certified.

Product Use: All statements, technical information and recommendations contained in this document are based on tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and perfomance of a 3M product in a particular application, including conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method o application.



3M Italia SpA Reparto ASD Abrasivi Industriali Via Norberto Bobbio,21 20069 – Pioltello Milano Tel: 02 7035 2529 Fax: 02 93660172

Data Sheet: CF-DC Issued 06/11 © 3M 2011. All rights reserved.