



## Scotch-Brite™ Hook and Loop Disc Availability

Product Code	Product Name	Mineral Type	Grade	Color	Diameters
SE-DH	SE Surface Conditioning Disc	A	FIN	Green/Blue	4-1/2"-48"
		A	MED	Maroon/Blue	1-1/2"-48"
		A	CRS	Brown/Blue	4"-48"

### Aggressiveness



### Finish



## TN Quick-change Discs\*

Product Code	Product Name	Mineral Type	Grade	Color	Diameters
SE-DN	TN Quick-Change SE Surface Conditioning Disc	A	FIN	Green/Blue	4-1/2", 5", 7"
		A	MED	Maroon/Blue	
		A	CRS	Brown/Blue	

\* Other combinations may be available upon special request.

## Scotch-Brite™ Roloc™ Disc Availability

Product Code	Product Name	Mineral Type	Grade	Color	Diameters
SE-DR	Roloc TR SE Surface Conditioning Disc	A	FIN	Green/Blue	1", 1-1/2", 2"
SE-DP	Roloc TP SE Surface Conditioning Disc	A	MED	Maroon/Blue	3", 4"
SE-DS	Roloc TS SE Surface Conditioning Disc	A	CRS	Brown/Blue	
SE-DM	Roloc TSM SE Surface Conditioning Disc	A	FIN	Green/Blue	1-1/2", 2", 3"
		A	MED	Maroon/Blue	
		A	CRS	Brown/Blue	

## Scotch-Brite™ SE Belt Availability

Product Code	Product Name	Mineral Type	Grade	Front Color	Back Color	Width	Length
SE-BS	SE Surface Conditioning Belt (scrim)	A	FIN	Green	Blue	1/4"	15"-24"
		A	MED	Maroon	Blue	1/2"-6"	9 1/2"-15"
		A	CRS	Brown	Blue	3/8"-3/4"	15"-168"
						3/4"-12"	15"-500"
						12"-18"	24"-500"
						18"-25"	48"-500"
SE-BL	SE Surface Conditioning LS Belt	A	FIN	Green	Blue	1/4"	15"-24"
		A	MED	Maroon	Blue	1/2"-6"	9 1/2"-15"
		A	CRS	Brown	Blue	3/8"-3/4"	15"-168"
						3/4"-12"	15"-500"
						12"-18"	24"-500"
						18"-25"	48"-500"
SE-BF	SE Surface Conditioning FB Belt	A	MED	Green	Blue	1"-18"	30"-500"
		A	CRS	Maroon	Blue	18"-26"	48"-500"
						26"-37"	60"-500"
						38"-50"	72"-500"

### Flexibility

Least	Most
<b>Film Back</b>	<b>Scrim</b>
<p>Slightly harder, less conformable than low stretch.</p> <p>Use with platens or stroke sanders.</p> <p>Use when application requires a smooth backed belt.</p>	<p>Next softest, conformable backing.</p> <p>Use with belts longer than 132".</p> <p>Use with belts wider than 18".</p>
	<p>Softest, most conformable backing.</p> <p>Use when conformability is required.</p> <p>Use when contact wheel diameter is less than 1".</p> <p>Use with "small" belt sizes.</p>

## SE A Fine Disc and Belt – Stock Items

UPC #	Description	Size	Case Quantity
048011-			
30006-1	SE-BS Surface Conditioning Belt	1/2" x 18"	20/CS
30007-8	SE-BS Surface Conditioning Belt	1/2" x 24"	20/CS
30008-5	SE-BS Surface Conditioning Belt	3 1/2" x 15 1/2"	10/CS
30005-4	SE-DR Roloc Surface Conditioning Belt	2"	200/CS
93453-2	SE-DR Roloc Surface Conditioning Belt	3"	200/CS
92743-5	SE-DH Surface Conditioning Belt	4.5" x NH	50/CS
30003-0	SE-DH Surface Conditioning Belt	7" x NH	25/CS

### IMPORTANT NOTICE TO PURCHASER

**Product Use:** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application. 3M warrants that its abrasive products will be free from defects in materials and manufacture. If an abrasive product is proved to be defective, then the exclusive remedy, and 3M's sole obligation shall be, at 3M's option, to replace the quantity of the product which is proved to be defective or to refund the purchase price.

**Warranty and Limited Remedy:** 3M makes no other warranties, express or implied, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, OF FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.

**Limitation of Liability:** 3M shall not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including, but not limited to, warranty, contract, negligence or strict liability. The foregoing Warranty and Limited Remedy and Limitation of Liability may be changed only by written agreement signed by authorized officers of 3M.

**Safety Information:** Always use appropriate protective glasses, face shields and body protection. Do not exceed maximum operating RPM's. Use guards provided with machine. Follow safety operation procedures posted in work areas.



### Abrasive Systems

3M Center, Building 223-6N-01  
St. Paul, MN 55144-1000

### 3M Canada

PO Box 5757  
London, Ontario,  
Canada N6A 4T1



Printed on 50% recycled waste paper,  
including 10% post-consumer waste paper.

© 3M IPC 2001 Litho in USA

61-5002-8013-8

# Scotch-Brite™

## SE A Fine Surface Conditioning Discs and Belts

*More durable and longer life for  
consistent and precise finish part after part*

**New**



With a choice of cut, finish, durability, and application method, Scotch-Brite™ Discs and Belts represent the widest selection of surface conditioning products for all types of metal.

Now to further expand your choice and capabilities, the SE category of Scotch-Brite surface conditioning products includes new SE A Fine discs and belts.

- Tougher and more aggressive non-woven web than regular Scotch-Brite surface conditioning products
- Extra cut and longer life for increased productivity and lower cost in deburring, grindline conditioning, surface preparation, and finishing
- Improve metal surfaces without significantly changing shape or dimension of the work piece
- Help prevent undercutting or gouging
- Provide consistent, uniform finish as fresh abrasive is continually exposed to the work surface
- Run cool and resist loading with open web construction, extending performance life

**3M** *Innovation*