



1/2" (13 MM) QUIET COMPOSITE IMPACT

Model No. 5350A

- Friction Ring Socket Retainer
- Reverse bias motor
- Twin hammer impact mechanism
- Three Level power control
- Lightweight composite housing
- Contoured trigger for comfort and control
- Grade 5 bolt capacity: 5/8" (16 mm)
- Drive Size: 1/2"
- Working torque: 100 - 450 ft./lbs. (135 - 610 Nm)
- Max. torque: 520 ft.lbs. (705 Nm)
- Free speed: 6300 RPM
- Blows per minute: 1200
- Weight: 4.6 lbs. (2.07 kg)
- Length: 6.7" (170 mm)
- Air inlet size: 1/4" NPT
- Low sound level 82 dB (A)
- Recommended hose size: 3/8" (10 mm)
- Average Air consumption: 3.9 cfm (1.8 l/s)



1/2" (13 MM) QUIET COMPOSITE IMPACT

Model No. 5350AP

- Pin Socket Retainer
- Reverse bias motor
- Twin hammer impact mechanism
- Three Level power control
- Lightweight composite housing
- Contoured trigger for comfort and control
- Grade 5 bolt capacity: 5/8" (16 mm)
- Drive Size: 1/2"
- Working torque: 100 - 450 ft./lbs. (135 - 610 Nm)
- Max. torque: 520 ft.lbs. (705 Nm)
- Free speed: 6300 RPM
- Blows per minute: 1200
- Weight: 4.6 lbs. (2.07 kg)
- Length: 6.7" (170 mm)
- Air inlet size: 1/4" NPT
- Low sound level 82 dB (A)
- Recommended hose size: 3/8" (10 mm)
- Average Air consumption: 3.9 cfm (1.8 l/s)



1/2" (13 MM) QUIET COMPOSITE IMPACT

Model No. 5350AL

- Pin Socket Retainer
- Reverse bias motor
- Twin hammer impact mechanism
- 2" extended anvil
- Three Level power control
- Lightweight composite housing
- Contoured trigger for comfort and control
- Grade 5 bolt capacity: 5/8" (16 mm)
- Drive Size: 1/2"
- Working torque: 100 - 450 ft./lbs. (135 - 610 Nm)
- Max. torque: 520 ft.lbs. (705 Nm)
- Free speed: 6300 RPM
- Blows per minute: 1200
- Weight: 4.8 lbs. (2.17 kg)
- Length: 8.7" (220 mm)
- Air inlet size: 1/4" NPT
- Low sound level 82 dB (A)
- Recommended hose size: 3/8" (10 mm)
- Average Air consumption: 3.9 cfm (1.8 l/s)



1/2" (13 MM) IMPACT WRENCH

Model No. 5250A

- Reverse bias power
- Pin style impact mechanism
- Oil bath lubrication
- Built-in power regulator
- Molded comfort grip
- Friction ring socket retainer
- Grade 5 bolt capacity: 5/8" (16 mm)
- Drive size: 1/2" (13 mm)
- Working torque: 50-375 ft lb (68-508 Nm)
- Max. torque: 525 ft lb (712 Nm)
- Free speed: 7000 rpm
- Blows per minute: 985
- Weight: 6 lb (2.7 kg)
- Length: 7.7" (196 mm)
- Recommended hose size: 3/8" (10 mm)
- Air Consumption: 3.5 cfm (100 l/s) avg. – 14 cfm (395 l/s) max.

