



RO2510-44FNC

## PERFORMANCE:

Power: 0.25 hp (0.19 kW)  
Speed: 10,000 rpm

## FEATURES:

Built-in Speed Control  
Ergonomic 24-Position Indexable Grip



## ORBITAL JITTERBUG SANDERS

Model Number	Paper Size		Orbit Diameter		Weight		Height		Air Consumption Free Speed		Sound Level
	in	mm	in	mm	lb	kg	in	mm	cfm	l/s	
0.25 hp (0.19 kW)											
RO2510-44FNC	3 ¾ x 4 ¼	95 x 105	⅜	3	1.8	0.8	3.5	90	13	6	81

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:** Parts List • Safety and Instruction Manual

**Accessories:** Sander Accessories, see pages 706-708



GO459-60SNP



GO459-80SRP

## PERFORMANCE:

Power: 0.45 hp (0.34 kW)  
Speed: 900 rpm

## FEATURES:

3/16" (5 mm) Orbit Diameter  
Built-in Speed Control  
Lever Throttle  
Vacuum & Remote Vacuum  
Ergonomic 24-Position Indexable Grip



## GEARED ORBITAL SANDERS

Model Number		Free Speed	Pad Size		Weight		Height		Air Consumption		Sound Level
PSA Pad	H & L Pad	rpm	in	mm	lb	kg	in	mm	cfm	l/s	dB(A)
0.45 hp (0.34 kW) Non-Vacuum											
GO459-60SNP	GO459-60SNH	900	6	150	4.4	2	5	127	15	7	82
GO459-80SNP	GO459-80SNH	900	8	200	4.4	2	5	127	15	7	82
0.45 hp (0.34 kW) Remote Vacuum											
GO459-60SRP	GO459-60SRH	900	6	150	4.4	2	5	127	15	7	82
GO459-80SRP	GO459-80SRH	900	8	200	4.4	2	5	127	15	7	82

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:** Parts List • Safety and Instruction Manual

**Accessories:** Sander Accessories, see pages 706-708