



SAS03S122-20



SAS05S232-20



SAS10A182-20



77016 Threaded Arbor



300 Series Collet

PERFORMANCE:

Power: 0.33 hp (0.25 kW) – 1 hp (0.75 kW)
Speed: 12,000 rpm – 23,000 rpm

FEATURES:

Lockoff Lever Throttle
Front, Rear, and Vacuum Exhaust
Comfort Grip

RIGHT ANGLE DISC SANDERS



Model Number	Free Speed	Weight		Length		Air Consumption		Sound Level	Spindle Thread
	rpm	lb	kg	in	mm	Free Speed	cfm		
0.3 hp (0.22 kW) – Lever Throttle									
SAS03S122-20	12,000	1.1	0.5	5.625	143	11	5.2	82.2	1/4"-20
SAS03S202-20	20,000	1.1	0.5	5.625	143	11	5.2	82.9	1/4"-20
0.5 hp (0.37 kW) – Lever Throttle									
SAS05S232-20	23,000	1.3	0.59	5.625	143	23	10.3	88.6	1/4"-20
1 hp (0.75 kW) – Lever Throttle									
SAS10A122-20	12,000	2.15	0.98	7.5	190	30	14	84.6	1/4"-20
SAS10A152-20	15,000	2.15	0.98	7.5	190	30	14	TBD	1/4"-20
SAS10A182-20	18,000	2.15	0.98	7.5	190	30	14	83.4	1/4"-20
SAS10A324	3200	TBD	TBD	TBD	TBD	35	17	TBD	3/8"-24

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Parts List • Safety and Instruction Manual • Support Handle (1 hp Models) • Spindle Wrenches, 300 Series Collet, 1/4"-20 Threaded Arbor

Accessories: Sander Accessories, see pages 706-708