



PERFORMANCE:

Power: 0.40 hp (0.30 kW)
Speed: 10,000 rpm

FEATURES:

3/16" (5 mm) Orbit Diameter
Built-in Speed Control
Aluminum Housing
Palm & Lever Throttle



658

600 SERIES RANDOM ORBITAL SANDERS

| Model Number | | Free Speed | Pad Size | | Orbit Diameter | | Weight | | Height | | Air Consumption | | Sound Level |
|---|-----------|------------|----------|-----|----------------|----|--------|-----|--------|-----|-----------------|-----|-------------|
| PSA Pad | H & L Pad | rpm | in | mm | in | mm | lb | kg | in | mm | cfm | l/s | dB(A) |
| 0.40 hp (0.30 kW) - Palm Throttle | | | | | | | | | | | | | |
| PS690 ¹ | | 10,000 | 5 | 125 | 3/16 | 5 | 2.9 | 1.3 | 4.2 | 107 | 20 | 9 | 85 |
| 697 ¹ | | 10,000 | 6 | 150 | 3/16 | 5 | 2.9 | 1.3 | 4.2 | 107 | 20 | 9 | 85 |
| 0.40 hp (0.30 kW) - Dual Action - Lever Throttle | | | | | | | | | | | | | |
| 658 ¹ | | 10,000 | 5 | 125 | 3/16 | 5 | 3.2 | 1.5 | 4.2 | 107 | 20 | 9 | 85 |

For remote vacuum ready add suffix V

¹Not CE Certified **General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Parts List • Safety and Instruction Manual • Backing Pad & Wrench

Accessories: Sander Accessories, see pages 706-708



SPS10P18



SDG10P18

PERFORMANCE:

Power: 1 hp (0.75 kW)
Speed: 6000 rpm – 21,000 rpm

FEATURES:

Trigger Start
Down-Handle Exhaust
Comfort Grip

PISTOL GRIP SANDERS



| Model Number | Free Speed | Weight | | Height | | Air Consumption | | Sound Level |
|--|------------|--------|-----|--------|-----|-----------------|-----|-------------|
| | rpm | lb | kg | in | mm | cfm | l/s | |
| 1 hp (0.75 kW) - 5" (125 mm) Diameter Backing Pad | | | | | | | | |
| SPS10P6 | 6000 | 1.7 | 0.8 | 4.5 | 115 | 35 | 17 | 80 |
| SPS10P18 | 18,000 | 1.7 | 0.8 | 4.5 | 115 | 35 | 17 | 80 |
| 1 hp (0.75 kW) - 1/4" Collet | | | | | | | | |
| SDG10P18 | 18,000 | 1.7 | 0.8 | 5.8 | 145 | 35 | 17 | 86.2 |
| SDG10P21 | 21,000 | 1.7 | 0.8 | 5.8 | 145 | 35 | 17 | 86.3 |

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Parts List • Safety and Instruction Manual • Comfort Grip

Accessories: Sander Accessories, see pages 706-708

