



SXG05S23



STXG10S23

PERFORMANCE:

Power: 0.5 hp (0.37 kW) – 1 hp (0.75 kW)
 Speed: 12,000 rpm – 23,000 rpm
 Collet Size: 1/4" (6 mm)

FEATURES:

Heavy duty double tapered collet
 Ergonomic comfort grip
 Teasing throttle for maximum control
 Lever throttle with lock-off
 Ball bearing construction
 Adjustable speed control

EXTENDED DIE GRINDERS

Model Number	Free Speed	Weight		Length		Sound Level	Air Consumption		Collet Size	Exhaust
	rpm	lb	kg	in	mm	dB(A)	cfm	l/s		
0.5 hp (0.37 kW) – Lever Throttle – Extended – 200 Series Collet										
SXG05S18	18,000	2.1	0.95	11	280	85.8	23	10.9	¼"	Rear
SXG05S18M6	18,000	2.1	0.95	11	280	86.7	23	10.9	6 mm	Rear
SXG05S23	23,000	2.1	0.95	11	280	89.8	23	10.9	¼"	Rear
SXG05S23M6	23,000	2.1	0.95	11	280	85.9	23	10.9	6 mm	Rear
0.5 hp (0.37 kW) – Extended Die Grinder Lever Throttle – 300 Series Collet										
SXG05S18S	18,000	2.1	0.95	11	280	86.7	23	10.9	¼"	Rear
SXG05S18M6S	18,000	2.1	0.95	11	280	86.7	23	10.9	6mm	Rear
SXG05S23S	23,000	2.1	0.95	11	280	85.9	23	10.9	¼"	Rear
SXG05S23M6S	23,000	2.1	0.95	11	280	85.9	23	10.9	6mm	Rear
1 hp (0.75 kW) – Lever Throttle – Extended – 200 Series Collet										
STXG10S12	12,000	2.2	1	12.1	308	84.5	30	14	¼"	Rear
STXG10S12M6	12,000	2.2	1	12.1	308	78	30	14	6 mm	Rear
STXG10S18	18,000	2.2	1	12.1	308	82	30	14	¼"	Rear
STXG10S18M6	18,000	2.2	1	12.1	308	78	30	14	6 mm	Rear
STXG10S23	23,000	2.2	1	12.1	308	78	30	14	¼"	Rear
STXG10S23M6	23,000	2.2	1	12.1	308	81.6	30	14	6 mm	Rear
1 hp (0.75 kW) – Lever Throttle – Extended – Cone Wheel										
STXG10S18CW	18,000	2.2	1	12.2	310	82	30	14	N/A	Rear

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Parts List • Safety and Instruction Manual • Collet & Wrenches • Collet Guard (1DS series)

Accessories: Grinder Accessories, see page 698

