



Lithium General Purpose Grease, 14 Wt Oz

No. SL3310 | Item# 1007904 | Case# 1007903

Product Description	A high purity, NLGI Grade 2 lithium based grease. Provides superior lubrication & durability in any weather and most temperatures. It is a versatile grease designed for light duty applications requiring a long grease life. Will not break down or run out.
Applications	Hinges, latches, overhead door tracks, open gears, chains, cables, slide conveyors, guide rails, cams, pistons, machinery, tools, & equipment. A break-in lubrication for bearings.
Unit Package Description	14 Ounce Cartridge
Brand	Sta-Lube
Generic Description 1	Lithium General Purpose Grease
Net Fill	14 Wt Oz
UPC Code	072213331004
Unit Dimensions	9.31H x 2.13W x 2.13D in
Units Per Case	10
Case Dimensions	9.5H x 4.5W x 11.38D in
Cases Per Pallet	150
Case Weight	11 lbs
I 2 of 5 Code	30072213331005
Appearance	Amber Semi-Solid to Solid Grease
Base Type	Lithium-12
Flash point (F)	435°F
Flash point (C)	224°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.9 at 60°F
NLGI Grade	2
Timken OK Load Lbs.	Not Determined
Plastic Safe	Not Determined
Evaporation Rate	Slow

Last revised: 5/14/2020

Page 1 of 2



Chemical Solutions to Keep You Moving™

f t+ d+ in m • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Working Temp (F)	0 to 250°F
Working Temp (C)	-18 to 121°C
4 Ball EP	Not Determined
4 Ball Wear	Not Determined
Drop Point	350°F
Elastomer Compatibility	Not Determined
Leakage	Not Determined
Low Temp Torque	Not Determined
Oil Separation	<10%
Oxidation Stability	5
Pour Point (F)	-15°F
Pour Point (C)	-26°C
ISO Viscosity Grade	150
Water Washout	<15%
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	Not Determined
VOC g/L (Consumer Product def)	Not Determined
VOC lbs/gal (Consumer Prod def)	Not Determined
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.