

CHNIKS TO Free ShrinkFIT Toolholders

Free ShrinkFIT Toolholders with your purchase of a ShrinkSTATION, ShrinkPRO, or Quencher!

5 FREE Holders with 00400 ShrinkSTATION



ShrinkSTATION Features:

- · Changes tools in 15-25 seconds
- Easy-to-use touch screen controls
- · Automatic cooling cycle using shop air

Bundle Value: \$8,520 Sale Price: \$6,200

8 FREE Holders with 00600 ShrinkPRO



ShrinkPRO Features:

- Changes tools in only 6-10 seconds
- · Automatic cooling cycle using shop air
- Touchscreen operation

Bundle Value: \$12,820
Sale Price: \$10,500

8 FREE Holders with 00500 Quencher



ShrinkPRO Features:

- · Changes tools in only 3 seconds
- Cools tools in under 30 seconds
- Touchscreen operation

Bundle Value: \$18,220 Sale Price: \$15,900

Mix & Match from dozens of Techniks ShrinkFIT Toolholders Scan the QR code or go to http://bit.ly/2bRYI7B to find the holders than meet your needs. CAT40 CAT50 **BT30 BT40** HSK63A **HSK63A SlimLINE**

HSK63F



HSK100A

CAT40 Precision ShrinkFIT Toolholders




Techniks Certified for accuracy and balance

ShrinkFIT Holder Features

- Maximum T.I.R. only 0.0001"
- Balanced 25,000 RPM at G2.5
- Comes with coolant-thru set screw installed

ShrinkFIT toolholders provide concentric clamping force of 10,000 lbs. or more directly on the cutting tool shank to reduce T.I.R. (runout). This is why operators are able to run faster and cutters last longer too.



CAT40 ShrinkFIT Holders

| Part No. | Description | d1 | d2 | d3 | L | 11 | thread | coolant screw | List Price |
|----------|------------------------|--------|-------|-------|-------|-------|-------------|---------------|------------|
| 29002 | CAT40 x 1/8" I.D 3.5" | 1/8" | .36" | .63" | 3.5" | .79" | M6 x 1.0P | 16081C-20 | 258.00 |
| 29006 | CAT40 x 3/16" I.D 3.5" | 3/16" | .43" | .70" | 3.5" | .79" | M6 x 1.0P | 16081C-20 | 258.00 |
| 29010 | CAT40 x 1/4" I.D 3" | 1/4" | .71" | .94" | 3" | 1.42" | M5 x 0.8P | 16080C-20 | 258.00 |
| 29016 | CAT40 x 5/16" I.D 3.5" | 5/16" | .79" | 1.06" | 3.5" | 1.42" | M6 x 1.0P | 16081C-20 | 258.00 |
| 29020 | CAT40 x 3/8" I.D 3" | 3/8" | .94" | 1.18" | 3" | 1.53" | M8 x 1.25P | 16082C-20 | 258.00 |
| 29025 | CAT40 x 7/16" - 3" | 7/16" | .94" | 1.18" | 3" | 1.62" | M10 x 1.5P | 16083C-20 | 258.00 |
| 29026 | CAT40 x 1/2" I.D 3" | 1/2" | 1.10" | 1.34" | 3" | 1.85" | M10 x 1.5P | 16083C-20 | 258.00 |
| 29032 | CAT40 x 5/8" I.D 3.75" | 5/8" | 1.06" | 1.34" | 3.75" | 1.97" | M12 x 1.75P | 16085C-20 | 258.00 |
| 29034 | CAT40 x 3/4" I.D 3" | 3/4" | 1.42" | 1.65" | 3" | 2.04" | M16 x 2.0P | 16089C-20 | 284.00 |
| 29040 | CAT40 x 1.0" I.D 3" | 1.0" | 1.81" | 2.04" | 3" | 2.28" | M20 x 2.0P | 16091C-20 | 284.00 |
| 29046 | CAT40 x 1-1/4" I.D 4" | 1-1/4" | 1.81" | 2.09" | 4" | 2.28" | M20 x 2.0P | 16091C-20 | 258.00 |

Mix & Match from dozens of Techniks ShrinkFIT Toolholders Click the links below to choose the FREE toolholders for your spindle CAT40 CAT40 CAT50 BT30 BT40 HSK63A HSK63A SlimLINE HSK100A HSK63F



CAT50 Precision ShrinkFIT Toolholders




Techniks Certified for accuracy and balance

Features

- Maximum T.I.R. only 0.0001"
- Balanced 25,000 RPM at G2.5
- Comes with coolant-thru set screw installed

ShrinkFIT toolholders provide concentric clamping force of 10,000 lbs. or more directly on the cutting tool shank to reduce T.I.R. (runout). This is why operators are able to run faster and cutters last longer too.



CAT50 ShrinkFIT Holders

| Part No. | Description | d1 | d2 | d3 | L | 11 | thread | coolant screw | List Price |
|----------|--------------------------|--------|-------|-------|-------|-------|-------------|---------------|------------|
| 29051 | CAT50 x 1/8" I.D 4" | 1/8" | .36" | .72" | 4" | .79" | M6 x 1.0P | 16081C-20 | 330.00 |
| 29052 | CAT50 x 3/16" I.D 3.54" | 3/16" | .42" | .74" | 3.54" | .79" | M6 x 1.0P | 16081C-20 | 247.00 |
| 29054 | CAT50 x 1/4" I.D 3.54" | 1/4" | .71" | 1.02" | 3.54" | 1.42" | M5 x 0.8P | 16080C-20 | 247.00 |
| 29056 | CAT50 x 5/16" I.D 3.54" | 5/16" | .79" | 1.06" | 3.54" | 1.42" | M6 x 1.0P | 16081C-20 | 247.00 |
| 29058 | CAT50 x 3/8" I.D 3.94" | 3/8" | .94" | 1.26" | 3.94" | 1.42" | M8 x 1.25P | 16082C-20 | 288.00 |
| 29060 | CAT50 x 1/2" I.D 3.94" | 1/2" | 1.10" | 1.34" | 3.94" | 1.85" | M10 x 1.5P | 16083C-20 | 288.00 |
| 29062 | CAT50 x 5/8" I.D 3.94" | 5/8" | 1.06" | 1.34" | 3.94" | 1.97" | M12 x 1.75P | 16085C-20 | 288.00 |
| 29064 | CAT50 x 3/4" I.D 4.13" | 3/4" | 1.42" | 1.65" | 4.13" | 2.04" | M16 x 2.0P | 16089C-20 | 330.00 |
| 29068 | CAT50 x 1.0" I.D 4.13" | 1" | 1.81" | 2.09" | 4.13" | 2.28" | M20 x 2.0P | 16091C-20 | 330.00 |
| 29072 | CAT50 x 1-1/4" I.D 4.13" | 1-1/4" | 1.81" | 2.09" | 4.13" | 2.28" | M20 x 2.0P | 16091C-20 | 330.00 |
| 29074 | CAT50 x 1-1/4" I.D 4.72" | 1-1/4" | 1.81" | 2.09" | 4.72" | 2.28" | M20 x 2.0P | 16091C-20 | 350.00 |

Mix & Match from dozens of Techniks ShrinkFIT Toolholders Click the links below to choose the FREE toolholders for your spindle CAT40 CAT40 CAT50 BT30 BT40 HSK63A HSK63A SlimLINE HSK100A HSK63F



BT30 Precision ShrinkFIT Toolholders




Techniks Certified for accuracy and balance

Features

- Maximum T.I.R. only 0.0001"
- Balanced 25,000 RPM at G2.5
- Comes with coolant-thru set screw installed

ShrinkFIT toolholders provide concentric clamping force of 10,000 lbs. or more directly on the cutting tool shank to reduce T.I.R. (runout). This is why operators are able to run faster and cutters last longer too.



BT30 ShrinkFIT Holders

| Part No. | Description | d1 | d2 | d3 | L | 12 | thread | coolant screw | List Price |
|----------|-------------------|------|-------|-------|----|-------|-------------|---------------|------------|
| 67250 | BT30 x 1/4"I.D 3" | 1/4" | 0.82" | 1.06" | 3" | 1.42" | M5 x 0.8P | 16082C-20 | 252.00 |
| 67375 | BT30 x 3/8"I.D 3" | 3/8" | 0.94" | 1.25" | 3" | 1.42" | M8 x 1.25P | 16082C-20 | 252.00 |
| 67500 | BT30 x 1/2"I.D 3" | 1/2" | 0.94" | 1.25" | 3" | 1.85" | M10 x 1.5P | 16083C-20 | 252.00 |
| 67625 | BT30 x 5/8"I.D 3" | 5/8" | 1.06" | 1.33" | 3" | 1.97" | M12 x 1.75P | 16085C-20 | 252.00 |
| 67750 | BT30 x 3/4"I.D 3" | 3/4" | 1.29" | 1.62" | 3" | 2.04" | M16 x 2.0P | 16089C-20 | 252.00 |






BT40 Precision ShrinkFIT Toolholders



Features

- Maximum T.I.R. only 0.0001"
- Balanced 25,000 RPM at G2.5
- Comes with coolant-thru set screw installed

ShrinkFIT toolholders provide concentric clamping force of 10,000 lbs. or more directly on the cutting tool shank to reduce T.I.R. (runout). This is why operators are able to run faster and cutters last longer too.



BT40 ShrinkFIT Holders Inch Size

| Part No. | Description | d1 | d2 | d3 | L | 12 | thread | coolant screw | List Price |
|------------|------------------------|--------|-------|-------|----|-------|-------------|---------------|------------|
| 39110 | BT40 x 3/16" I.D 3.54 | 3/16" | .43" | .75" | 6" | .79" | M6 x 1.0P | 16081C-20 | 304.00 |
| 39111 | BT40 x 1/4" I.D 3.54 | 1/4" | .82" | 1.06" | 6" | 1.42" | M5 x 0.8P | 16080C-20 | 304.00 |
| 39113 | BT40 x 3/8" l.D 3.54 | 3/8" | .94" | 1.25" | 6" | 1.65" | - | 16082C-20 | 258.00 |
| 39114 | BT40 x 1/2" I.D 3.54 | 1/2" | 1.10" | 1.34" | 6" | 1.85" | M10 x 1.5P | 16083C-20 | 258.00 |
| 19029 | BT40 x 5/8" I.D 3.54 | 5/8" | 1.06" | 1.34" | 6" | 1.96" | M12 x 1.75P | 16089C-20 | 371.00 |
| 39115 | BT40 x 3/4"I.D 3.54 | 3/4" | 1.29" | 1.65" | 6" | 2.04" | M16 x 2.0P | 16085C-20 | 304.00 |
| 39117 | BT40 x 1.0" l.D 3.54 | 1.0" | 1.73" | 2.08" | 6" | 2.28" | M20 x 2.0P | 16089C-20 | 304.00 |
| 39119-4.13 | BT40 x 1-1/4" I.D 4.13 | 1-1/4" | 1.81" | 2.08" | 6" | 2.28" | M20 x 2.0P | 16091C-20 | 312.00 |





HSK63A Precision ShrinkFIT Toolholders




Techniks Certified for accuracy and balance

Features

- Maximum T.I.R. only 0.0001"
- Balanced 25,000 RPM at G2.5
- Comes with coolant-thru set screw installed

ShrinkFIT toolholders provide concentric clamping force of 10,000 lbs. or more directly on the cutting tool shank to reduce T.I.R. (runout). This is why operators are able to run faster and cutters last longer too.



HSK63A Inch Size ShrinkFIT Toolholders

| Part No. | Description | d1 | d2 | d3 | L | l1 | thread | coolant screw | List Price |
|----------|---------------------------|--------|-------|-------|-------|-------|-------------|---------------|------------|
| 93115 | HSK63A x 1/4" I.D 3.15" | 1/4" | .83" | 1.06" | 3.15" | 1.42" | M5 x 0.8P | 16082C-20 | 314.00 |
| 93116 | HSK63A x 5/16" I.D 3.15" | 5/16" | .83" | 1.06" | 3.15" | 1.42" | M6 x 1.0P | 16082C-20 | 314.00 |
| 93117 | HSK63A x 3/8" I.D 3.35" | 3/8" | .94" | 1.26" | 3.35" | 1.65" | M8 x 1.25P | 16082C-20 | 314.00 |
| 93118 | HSK63A x 7/16" I.D 3.54" | 7/16" | .94" | 1.26" | 3.54" | 1.85" | M8 x 1.25P | 16082C-20 | 314.00 |
| 93119 | HSK63A x 1/2" I.D 3.54" | 1/2" | .94" | 1.26" | 3.54" | 1.85" | M10 x 1.5P | 16083C-20 | 314.00 |
| 93120 | HSK63A x 9/16" I.D 3.54" | 9/16" | 1.06" | 1.34" | 3.54" | 1.85" | M10 x 1.5P | 16083C-20 | 314.00 |
| 93121 | HSK63A x 5/8" I.D 3.74" | 5/8" | 1.06" | 1.34" | 3.74" | 1.97" | M12 x 1.75P | 16085C-20 | 314.00 |
| 93124 | HSK63A x 3/4" I.D 3.94" | 3/4" | 1.30" | 1.65" | 3.94" | 2.05" | M16 x 2.0P | 16089C-20 | 314.00 |
| 93126 | HSK63A x 1.0" I.D 4.53" | 1.0" | 1.73" | 2.05" | 4.53" | 2.28" | M20 x 2.0P | 16091C-20 | 314.00 |
| 93128 | HSK63A x 1-1/4" I.D 4.72" | 1-1/4" | 1.73" | 2.09" | 4.72" | 2.28" | M20 x 2.0P | 16091C-20 | 314.00 |

Mix & Match from dozens of Techniks ShrinkFIT Toolholders Click the links below to choose the FREE toolholders for your spindle CAT40 CAT50 BT30 BT40 HSK63A HSK63A SlimLINE HSK100A HSK63F



HSK63A SlimLINE ShrinkFIT Toolholders




Use SlimLINE holders for finish passes where small nose diameter (d2) tooling is required.

SlimLINE Features

- Smaller nose diameter (d2)
- Maximum T.I.R. only 0.0001"
- Balanced 25,000 RPM at G2.5

ShrinkFIT toolholders provide concentric clamping force of 10,000 lbs. or more directly on the cutting tool shank to reduce T.I.R. (runout). This is why operators are able to run faster and cutters last longer too.



HSK63A SlimLINE ShrinkFIT Holders

| Part No. | Description | d1 | d2 | d3 | L | 11 | thread | coolant screw | List Price |
|----------|-----------------------------------|-------|------|-------|-------|-------|----------|---------------|------------|
| 73528 | HSK63A x 1/8" I.D 3.15" SlimLINE | 1/8" | .35" | .63" | 3.15" | .78" | M6x1.0P | 16081C-20 | 276.00 |
| 73538 | HSK63A x 3/16" I.D 3.15" SlimLINE | 3/16" | .43" | .69" | 3.15" | .78" | M6x1.0P | 16081C-20 | 276.00 |
| 73548 | HSK63A x 1/4" I.D 3.15" SlimLINE | 1/4" | .47" | .81" | 3.15" | 1.42" | M5x0.8P | 16080C-20 | 276.00 |
| 73568 | HSK63A x 3/8" I.D 3.15" SlimLINE | 3/8" | .63" | .94" | 3.15" | 1.65" | M8x1.25P | 16082C-20 | 276.00 |
| 73588 | HSK63A x 1/2" I.D 3.15" SlimLINE | 1/2" | .71" | 1.06" | 3.15" | 1.85" | M10x1.5P | 16083C-20 | 276.00 |





HSK100A Precision ShrinkFIT Toolholders




Techniks Certified for accuracy and balance

Features

- Maximum T.I.R. only 0.0001"
- Balanced 25,000 RPM at G2.5
- Comes with coolant-thru set screw installed

ShrinkFIT toolholders provide concentric clamping force of 10,000 lbs. or more directly on the cutting tool shank to reduce T.I.R. (runout). This is why operators are able to run faster and cutters last longer too.



HSK100A ShrinkFIT Toolholders

| Part No. | Description | d1 | d2 | d3 | 11 | 12 | thread | coolant screw | List Place |
|----------|----------------------------|--------|-------|-------|-------|-------|-------------|---------------|------------|
| 39304 | HSK100A x 1/8" I.D 3.54" | 1/8" | .35" | .87" | 3.54" | .79" | M6 x 1.0P | 16081C-20 | 464.00 |
| 39306 | HSK100A x 1/4" I.D 3.54" | 1/4" | .83" | 1.06" | 3.54" | 1.42" | M5 x 0.8P | 16080C-20 | 464.00 |
| 39308 | HSK100A x 5/16" I.D 3.35" | 5/16" | .79" | 1.06" | 3.35" | 1.42" | M6 x 1.0P | 16081C-20 | 464.00 |
| 39310 | HSK100A x 3/8" I.D 3.54" | 3/8" | .94" | 1.26" | 3.54" | 1.65" | M8 x 1.25P | 16082C-20 | 464.00 |
| 39312 | HSK100A x 7/16" I.D 3.74" | 7/16" | .94" | 1.26" | 3.74" | 1.85" | M10 x 1.5P | 16083C-20 | 464.00 |
| 39314 | HSK100A x 1/2" I.D 3.74" | 1/2" | 1.10" | 1.34" | 3.74" | 1.85" | M10 x 1.5P | 16083C-20 | 464.00 |
| 39318 | HSK100A x 5/8" I.D 3.94" | 5/8" | 1.06" | 1.34" | 3.94" | 1.97" | M12 x 1.75P | 16085C-20 | 464.00 |
| 39320 | HSK100A x 3/4" I.D 4.13" | 3/4" | 1.42" | 1.65" | 4.13" | 2.04" | M16 x 2.0P | 16089C-20 | 464.00 |
| 39324 | HSK100A x 1.0" I.D 4.53" | 1.0" | 1.81" | 2.09" | 4.53" | 2.28" | M20 x 2.0P | 16091C-20 | 464.00 |
| 39326 | HSK100A x 1-1/4" I.D 4.72" | 1-1/4" | 1.81" | 2.09" | 4.72" | 2.28 | M20 x 2.0P | 16091C-20 | 464.00 |

Mix & Match from dozens of Techniks ShrinkFIT Toolholders Click the links below to choose the FREE toolholders for your spindle CAT40 CAT40 CAT50 BT30 BT40 HSK63A HSK63A SlimLINE HSK100A HSK63F



HSK63F Precision ShrinkFIT Toolholders




Techniks Certified for accuracy and balance

Features

- Maximum T.I.R. only 0.0001"
- Balanced 25,000 RPM at G2.5
- Comes with coolant-thru set screw installed

ShrinkFIT toolholders provide concentric clamping force of 10,000 lbs. or more directly on the cutting tool shank to reduce T.I.R. (runout). This is why operators are able to run faster and cutters last longer too.



HSK63F Inch ShrinkFIT Toolholders

| Part No. | Description | d1 | d2 | d3 | l1 | 12 | thread | coolant screw | List Price |
|----------|--------------------------|-------|-------|-------|-------|-------|-------------|---------------|------------|
| 71250 | HSK63F x 1/4" I.D 3.15" | 1/4" | .83" | 1.06" | 3.15" | 1.42" | M5 x 0.8P | 16080C-20 | 288.00 |
| 71312 | HSK63F x 5/16" I.D 3.74" | 5/16" | .79" | 1.06" | 3.74" | 1.42" | M6 x 1.0P | 16081C-20 | 361.00 |
| 71375 | HSK63F x 3/8" I.D 3.74" | 3/8" | .94" | 1.26" | 3.74" | 1.65" | M8 x 1.25P | 16082C-20 | 288.00 |
| 71500 | HSK63F x 1/2" I.D 3.74" | 1/2" | .94" | 1.26" | 3.74" | 1.85" | M10 x 1.5P | 16083C-20 | 288.00 |
| 71625 | HSK63F x 5/8" x 3.74" | 5/8" | 1.06" | 1.34" | 3.74" | 1.97" | M12 x 1.75P | 16085C-20 | 361.00 |
| 71750 | HSK63F x 3/4" I.D 3.94" | 3/4" | 1.42" | 1.65" | 3.94" | 2.05" | M16 x 2.0P | 16089C-20 | 288.00 |
| 71100 | HSK63F x 1.0" I.D 4.53" | 1" | 1.42" | 1.65" | 4.53" | 2.28" | M20 x 2.0P | 16091C-20 | 288.00 |

Mix & Match from dozens of Techniks ShrinkFIT Toolholders Click the links below to choose the FREE toolholders for your spindle CAT40 CAT50 BT30 BT40 HSK63A HSK63A SlimLINE HSK100A HSK63F

