## **OE315 NS**

## Vegetable Ester Based Cutting Oil

TRIM<sup>®</sup> OE315 NS is a heavy-duty straight cutting oil formulated using renewable vegetable esters. For use in very tough machining operations of hardened steel alloys, tool steels and stainless steels. TRIM OE315 NS is especially effective in deep hole drilling applications due to its reasonably low viscosity, lubricity and EP performance.

### Straight Oils



#### Straight to the point-of-cut:

TRIM® straight oils, used "straight up", without dilution of water, provide maximum lubricity. Typically used for operations such as Swissstyle screw machines, honing, grinding very difficult to machine materials, and gun drilling.

Depending on the specific product, some TRIM straight oils are a highend blend of various base oils, while others contain extreme pressure additives to control built-up edge and for added tool life.

Get straight to the cut with TRIM straight oils.



#### **Choose OE315 NS:**

- Excellent extreme-pressure additive package for efficient metal removal
- Extremely high lubricity ensures fantastic tool life
- Low viscosity ensures excellent chip removal in deep-hole drilling
- Ester based formulation ensures very low misting potential
- Very high flash point
- · Good oxidation stability
- Compatible with copper containing alloys
- Light color and low odor for good operator acceptance

#### **OE315 NS especially for:**

**Applications** — deep hole drilling, drilling, gear cutting, gun drilling, milling, reaming, tapping, and turning

**Metals** — aluminum, Inconel<sup>®</sup>, nickel alloys, stainless steels, steel alloys, titanium, and yellow metals

**Industries** — aerospace, automotive, general industry, and medical

**OE315 NS is free of** — chlorine and zinc

#### **Health and Safety**

See the most recent SDS at https://2trim.us/s/?i=2732-en-US-US



# **OE315 NS**

## Vegetable Ester Based Cutting Oil

### **Application Guidelines**

- TRIM OE315 NS is designed to be used straight.
- For additional product application information, including performance optimization, please contact your Master Fluid Solutions' Authorized Distributor at <a href="https://www.2trim.us/distributors.php">https://www.2trim.us/distributors.php</a>, your District Sales Manager, or call our Tech Line at 1-800-537-3365.

#### **Physical Properties Typical Data**

Color Odor Form Flash Point Viscosity Straw yellow Mild Liquid > 446°F

15.00 cSt @104°F (40°C)









TRIM® OE315 NS | ©2012-2019 Master Fluid Solutions® | 2019-01-17



#### **Additional Information**

- Before using on any metals or applications not specifically recommended, consult Master Fluid Solutions.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.

TRIM® is a registered trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

https://2trim.us/di/?plr=OE315NS\*en-us\*na



Master Fluid Solutions 501 West Boundary Street Perrysburg, OH 43551-1200 USA

+1 419-874-7902 info@masterchemical.com masterfluidsolutions.com/na/en-us/