



TRIM[®] OH200

Superfinish and Honing Oil

GENERAL DESCRIPTION

TRIM[®] OH200 is a medium-duty honing and superfinishing straight oil for alloy steels. OH200 can also be used for tapping and reaming of cast iron and aluminum alloys.

ADVANTAGES

- Good lubricity
- Will not stain copper alloys
- High flash point
- Contains no kerosene
- Copper Corrosion Test: Inactive at 212°F, 100°C, 1 hour

APPLICATION GUIDELINES

- Packaging: North America – 1-gallon jug, 5-gallon pail, 54-gallon drum, and 270-gallon tote bin.
- Packaging: Europe/Asia – 20-litre pail, 204-litre drum, and 1000-litre IBC.
- For additional product applications information including performance optimization, please contact your Master Chemical Authorized Distributor at 2trim.us/distributors.php, your District Sales Manager, the Tech Line at 1-800-537-3365, or visit our website at www.masterchemical.com.

HEALTH AND SAFETY

See the most recent SDS at 2trim.us/s/?i=1083-en-US-US.



PHYSICAL PROPERTIES (TYPICAL DATA)

Color.....	Dark Red	Specific Gravity.....	0.860
Odor	Oily	Viscosity	5.7 cSt @ 40°C
Form.....	Liquid	V.O.C. Content (ASTM E1868-10).....	267.5 g/l
Flash Point	216°F (102°C) (COC)		

The information herein is given in good faith and believed current as of the date of this Data & Information sheet and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Chemical Corporation for further information. For the most recent version of this document, please go to this

URL: 2trim.us/di/?i=44

TRIM[®] is a registered trademark of Master Chemical Corporation

© 2012-2016 Master Chemical Corporation • Revised February 18, 2016