

Carbide End Mills

YOUR #1 SOURCE FOR AMERICAN-MADE PREMIUM CUTTING TOOLS



4 FLUTE - EXTRA LONG LENGTH - R_1 CORNER RADIUS - 30° HELIX



SERIES 746
ALTiN COATED

DIA	SHANK	LOC	OAL	RAD	ITEM #	LIST PRICE
1/8	1/8	1	3	0.015	TC74601	36.83
1/8	1/8	1	3	0.020	TC74602	36.83
1/8	1/8	1	3	0.030	TC74603	36.83
3/16	3/16	1-1/8	3	0.015	TC74604	40.34
3/16	3/16	1-1/8	3	0.020	TC74605	40.34
3/16	3/16	1-1/8	3	0.030	TC74606	40.34
1/4	1/4	1-1/2	4	0.015	TC74607	56.12
1/4	1/4	1-1/2	4	0.020	TC74608	56.12
1/4	1/4	1-1/2	4	0.030	TC74609	56.12
1/4	1/4	1-1/2	4	0.045	TC74610	56.12
1/4	1/4	1-1/2	4	0.060	TC74611	56.12
1/4	1/4	1-1/2	6	0.015	TC74612	75.41
1/4	1/4	1-1/2	6	0.020	TC74613	75.41
1/4	1/4	1-1/2	6	0.030	TC74614	75.41
1/4	1/4	1-1/2	6	0.045	TC74615	75.41
1/4	1/4	1-1/2	6	0.060	TC74616	75.41
5/16	5/16	1-5/8	4	0.015	TC74617	77.17
5/16	5/16	1-5/8	4	0.020	TC74618	77.17
5/16	5/16	1-5/8	4	0.030	TC74619	77.17
5/16	5/16	1-5/8	4	0.045	TC74620	77.17
5/16	5/16	1-5/8	4	0.060	TC74621	77.17
3/8	3/8	1-3/4	4	0.015	TC74622	84.18
3/8	3/8	1-3/4	4	0.020	TC74623	84.18
3/8	3/8	1-3/4	4	0.030	TC74624	84.18
3/8	3/8	1-3/4	4	0.045	TC74625	84.18
3/8	3/8	1-3/4	4	0.060	TC74626	84.18
3/8	3/8	1-1/2	6	0.015	TC74627	119.26
3/8	3/8	1-1/2	6	0.020	TC74628	119.26
3/8	3/8	1-1/2	6	0.030	TC74629	119.26
3/8	3/8	1-1/2	6	0.045	TC74630	119.26
3/8	3/8	1-1/2	6	0.060	TC74631	119.26
1/2	1/2	1-1/2	6	0.015	TC74632	180.64
1/2	1/2	1-1/2	6	0.020	TC74633	180.64
1/2	1/2	1-1/2	6	0.030	TC74634	180.64
1/2	1/2	1-1/2	6	0.045	TC74635	180.64
1/2	1/2	1-1/2	6	0.060	TC74636	180.64
1/2	1/2	1-1/2	6	0.090	TC74637	180.64
1/2	1/2	1-1/2	6	0.125	TC74638	180.64
1/2	1/2	3	6	0.015	TC74639	189.41
1/2	1/2	3	6	0.020	TC74640	189.41

DIA	SHANK	LOC	OAL	RAD	ITEM #	LIST PRICE
1/2	1/2	3	6	0.030	TC74641	189.41
1/2	1/2	3	6	0.045	TC74642	189.41
1/2	1/2	3	6	0.060	TC74643	189.41
1/2	1/2	3	6	0.090	TC74644	189.41
1/2	1/2	3	6	0.125	TC74645	189.41
5/8	5/8	3	6	0.015	TC74646	266.57
5/8	5/8	3	6	0.020	TC74647	266.57
5/8	5/8	3	6	0.030	TC74648	266.57
5/8	5/8	3	6	0.045	TC74649	266.57
5/8	5/8	3	6	0.060	TC74650	266.57
5/8	5/8	3	6	0.090	TC74651	266.57
3/4	3/4	3	6	0.015	TC74652	365.77
3/4	3/4	3	6	0.020	TC74653	365.77
3/4	3/4	3	6	0.030	TC74654	365.77
3/4	3/4	3	6	0.045	TC74655	365.77
3/4	3/4	3	6	0.060	TC74656	365.77
3/4	3/4	3	6	0.090	TC74657	365.77
3/4	3/4	3	6	0.125	TC74658	365.77
3/4	3/4	4	7	0.015	TC74659	600.74
3/4	3/4	4	7	0.020	TC74660	600.74
3/4	3/4	4	7	0.030	TC74661	600.74
3/4	3/4	4	7	0.045	TC74662	600.74
3/4	3/4	4	7	0.060	TC74663	600.74
3/4	3/4	4	7	0.090	TC74664	600.74
3/4	3/4	4	7	0.125	TC74665	600.74
1	1	3	6	0.015	TC74666	596.11
1	1	3	6	0.020	TC74667	596.11
1	1	3	6	0.030	TC74668	596.11
1	1	3	6	0.045	TC74669	596.11
1	1	3	6	0.060	TC74670	596.11
1	1	3	6	0.090	TC74671	596.11
1	1	3	6	0.125	TC74672	596.11
1	1	4	7	0.015	TC74673	859.35
1	1	4	7	0.020	TC74674	859.35
1	1	4	7	0.030	TC74675	859.35
1	1	4	7	0.045	TC74676	859.35
1	1	4	7	0.060	TC74677	859.35
1	1	4	7	0.090	TC74678	859.35
1	1	4	7	0.125	TC74679	859.35

For coating information see page 6. For technical information, please see pages 224, 228-229.

TOLERANCES	DIAMETER	SHANK	RADIUS
1/8" - 1/2"	+0.00, -0.02	-0.001, -0.004 ISO H8	+0.01, -0.01
5/8" - 1"	+0.00, -0.03	-0.001, -0.004 ISO H8	+0.01, -0.01