Science. Applied to Life.™



Comfort and versatility with the 3M™ Versaflo™ TR-300N+ PAPR.

Increased stock now available!

Our 3MTM VersafloTM TR-300+ PAPR System for particulate environments provides great versatility, comfort and ease of use. Production has ramped up tenfold in order to meet pandemic demand.

Meet the 3M[™] Versaflo[™] TR-300+ Powered Air Purifying Respirator.

Comfort All Day Long

- Constant airflow: even as the battery discharges, or the filter becomes loaded with particulates, the unit delivers a steady flow of air
- High capacity battery (TR-332) lasts 8-12 hrs
- Two airflow rate options

Ease of Use

- Fit testing is not required with loose fitting headtops and those with limited facial hair may be accommodated
- User-friendly interface: monitor the operating status of your filter, battery, and airflow at a glance
- Audio and visual alarms for filter load and low battery
- Colour-indicated, interactive touch points

Straightforward, Minimal Maintenance

Most maintenance can be done quickly and easily by hand, including changing the battery, filter and pre-filter.

- 3M[™] Versaflo[™] Easy Clean Belt TR-327 and blower unit have smooth surfaces, facilitating fast wipe-downs for easier cleaning
- IP53 rating Suitable for use in decontamination showers
- Brushless motor for up to 5,000 hours of run time*
- * Estimated depending on use conditions

3M™ Versaflo™ TR-300N+ ECK (Easy Clean Kit) and Consumables

A complete, ready-to-use High Efficiency PAPR system, optimized for healthcare, pharmaceutical, and food and beverage applications.

Suggested for healthcare and food and beverage applications.



Easy Clean PAPR Kit - TR-300N+ ECK

- S-433L Hood Assembly
- **BT-30 Length Adjusting Breathing Tube**
- TR-302N+ PAPR Unit
- TR-327 Easy Clean Belt
- **TR-332 High Capacity Battery**
- TR-341N Battery Charger Kit
- TR-3712N HE Filter
- TR-3600 Pre-Filter
- **TR-971 Airflow Indicator**

TR-300N+ ECK

S-133 Series



S-Series Hoods with Increased Availability

Part Numbers	Size	Assigned Protection Factor (APF)	Suspension	Sealing Surface	Inner Shroud
S-133S-5	S/M	25	Integrated	Face	No
S-133L-5	M/L	25	integrated	race	INO
S-433S-5	S/M	1000	Intograted	Face	No
S-433L-5	M/L	1000	Integrated		INO

S-433 Series *Kit comes with S-433L



Sizing General Guidelines for S-Series Hoods and Headcovers

oizing deficial dalidelines for 0 defices floods and fleadcovers															
Head Circumference (cm)	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64
US Hat Size	6 1/4	6 3/8	6 1/2	6 5/8	6 3/4	6 7/8	7	7 1/8	7 1/4	7 3/8	7 1/2	7 5/8	7 3/4	7 7/8	8
S/M															
M/L			·												

Replacement High Efficiency Filters



Product	Case Qty
TR-3712N-5	5
TR-3712N-40	40

For more information, visit 3M.ca/TR-300ECK.

Personal Safety Division 3M Canada P.O. Box 5757 London, Ontario N6A 4T1

1-800-267-4414 3M.ca/Safety

WARNING

These respirators help reduce exposures to certain airborne particulates. Before use, the wearer must read and understand the User Instructions provided as a part of the product packaging. A written respiratory protection program must be implemented meeting all the requirements of OSHA 1910.134 including training, fit testing and medical evaluation. In Canada, CSA standards Z94.4 requirements must be met and/or requirements of the applicable jurisdiction, as appropriate. Misuse may result in injury, illness or death. For correct use, consult supervisor and User Instructions, or call 3M PSD Technical Service in Canada at 1-800-267-4414.

3M PSD products are for occupational use only.

3M, 3M Science. Applied to Life. and Versaflo are trademarks of 3M. Used under license in Canada. © 2020, 3M. All rights reserved. 2008-18044 E