



Brite®Zinc®, 12.5 Wt Oz

No. B-100 | Item# 1008302 | Case# 1008223

Product Description One step color matches the shiny look of hot dip

galvanizing. 69% zinc metal. Special no clog nozzle. Covers up to 32 square feet. Meets requirements of

ASTM-A780 for corrosion protection.

Color Gray

Applications For parts and assemblies to be top-coated.

Unit Package Description 16 Ounce Aerosol

Brand Weld-Aid

Generic Description 1 Corrosion Inhibitor

Net Fill 12.5 Wt Oz

UPC Code 731592100013

Unit Dimensions 8.00H x 2.50W x 2.50D in

Units Per Case 12

Case Dimensions 8.75H x 8.25W x 11.00D in

Cases Per Pallet 76

Case Weight 14.25 lbs

I 2 of 5 Code 30731592100014

Appearance Gray Liquid

Flash point (F) $-4^{\circ}F$ Flash point (C) $-20^{\circ}C$

Flammability Class - CPSC Extremely Flammable Aerosol

Plastic Safe Not Determined

Evaporation Rate Moderate

pH Not Applicable

Dry Time - Fully Dry 24 Hours

Dry Time - Tack Free 15 Minutes

Recoat 15 Minutes

Coverage Not Determined

Dielectric Strength Not Determined

Last revised: 5/1/2020

Page 1 of 2







Working Temp (F) Not Determined
Working Temp (C) Not Determined
Propellant Propane, Butane

Aerosol Flammability Level II VOC % (Consumer Product 46.6 def)

VOC g/L (Consumer 382.1 Product def)

VOC lbs/gal (Consumer 3.2 Prod def)

VOC Category Aerosol Coating: Metallic Coating

MIR Limit (EPA) 1.9
MIR Limit (CA) 1.25
MIR Value 1.11

Removal (How To) Remove with paint stripper or other solvent.

Last revised: 5/1/2020

Page 2 of 2

