

S803HA

Slot Drill



d ₁ R mm	Ch ±0.03x45° mm	d ₂ R _{h6} mm	l ₂ mm	l ₁ mm	z	e-code	USD
1.00	-	3	3	38	3	S803HA1.0	55.40
1.50	-	3	3	38	3	S803HA1.5	55.40
1.80	-	6	3	50	3	S803HA1.8	58.30
2.00	-	6	3	50	3	S803HA2.0	53.60
2.50	0.08	6	3	50	3	S803HA2.5	56.60
2.80	0.08	6	4	50	3	S803HA2.8	59.50
3.00	0.08	6	4	50	3	S803HA3.0	53.60
3.50	0.08	6	4	50	3	S803HA3.5	59.50
3.80	0.08	6	5	54	3	S803HA3.8	65.40
4.00	0.13	6	5	54	3	S803HA4.0	58.30
4.50	0.13	6	5	54	3	S803HA4.5	65.40
4.80	0.13	6	6	54	3	S803HA4.8	65.40
5.00	0.13	6	6	54	3	S803HA5.0	59.50
5.75	0.13	6	7	54	3	S803HA5.75	65.40
6.00	0.13	6	7	54	3	S803HA6.0	59.50
6.75	0.13	8	8	58	3	S803HA6.75	89.30
7.00	0.13	8	8	58	3	S803HA7.0	89.30
7.75	0.13	8	9	58	3	S803HA7.75	95.20
8.00	0.20	8	9	58	3	S803HA8.0	1) 83.30
9.00	0.20	10	10	66	3	S803HA9.0	1) 119.00
9.70	0.20	10	11	66	3	S803HA9.7	1) 119.00
10.00	0.20	10	11	66	3	S803HA10.0	1) 110.00
11.70	0.20	12	12	73	3	S803HA11.7	1) 167.00
12.00	0.20	12	12	73	3	S803HA12.0	1) 151.00
13.70	0.20	14	14	75	3	S803HA13.7	1) 209.00

d ₁ R mm	Ch ±0.03x45° mm	d ₂ R _{h6} mm	l ₂ mm	l ₁ mm	z	e-code		USD
14.00	0.20	14	14	75	3	S803HA14.0	1)	191.00
15.70	0.20	16	16	82	3	S803HA15.7	1)	267.00
16.00	0.20	16	16	82	3	S803HA16.0	1)	249.00
17.70	0.20	18	18	84	3	S803HA17.7	1)	328.00
18.00	0.20	18	18	84	3	S803HA18.0	1)	322.00
19.70	0.30	20	20	92	3	S803HA19.7	1)	446.00
20.00	0.30	20	20	92	3	S803HA20.0	1)	387.00

¹⁾± 0.05x45° mm