



**TOLERANCES (mm)**

**1–2,5 DIAMETER**

$D_1 = +0,000/-0,025$

$D_2 = h_6$

**>2,5–6 DIAMETER**

$D_1 = +0,000/-0,030$

$D_2 = h_6$

**>6–10 DIAMETER**

$D_1 = +0,000/-0,040$

$D_2 = h_6$

**>10–20 DIAMETER**

$D_1 = +0,000/-0,050$

$D_2 = h_6$

## 56MB

METRIC SERIES

TECH INFO 66

mm						EDP NO.
CUTTING DIAMETER $D_1$	LENGTH OF CUT $L_2$	OVERALL LENGTH $L_1$	SHANK DIAMETER $D_2$	$\alpha$	REACH $L_3$	TI-NAMITE-A (AITiN)
1,0	1,0	76,0	6,0	8°10'	2,0	91349
1,5	1,5	76,0	6,0	7°45'	3,0	91350
2,0	2,0	76,0	6,0	7°10'	4,0	91351
2,5	2,5	76,0	6,0	6°35'	5,0	91352
3,0	3,0	76,0	6,0	6°	6,0	91353
4,0	4,0	76,0	6,0	4°30'	8,0	91354
5,0	5,0	89,0	6,0	2°30'	10,0	91355
6,0	6,0	89,0	6,0	–	12,0	91356
8,0	8,0	102,0	8,0	–	16,0	91357
10,0	10,0	102,0	10,0	–	20,0	91358
12,0	12,0	114,0	12,0	–	24,0	91359
16,0	16,0	140,0	16,0	–	32,0	91360
20,0	20,0	165,0	20,0	–	40,0	91361

Neck Option Available

- STEELS
- HARDENED STEELS