## PETRO-GARD® HI-VIS FR/ARC-RATED SAFETY JACKET - HI-VIS ORANGE - M



Product # V2246450A-M | Model # J160 400A

The Ranpro® 100% waterproof Hi-Vis Petro-Gard® FR/ARC-Rated Safety Jacket is made with low smoke Neoprene on Dupont™ Nomex® material, and provides superior, heavy-duty 100% waterproof, abrasion, puncture, and tear-resistant protection. StarTech® FR reflective tape offers superior visibility and safety in low-light conditions.

- Material The Ranpro High Visibility Petro-Gard®
   FR/ARC-Rated Safety Jacket is made with 14 oz/yd² low smoke
   Neoprene on Dupont™ Nomex® material, and provides
   superior, heavy-duty 100% waterproof, abrasion-, puncture-,
   and tear-resistant protection.
- ARC and Flame-resistant The fabric of the jacket meets FR
   ASTM F1891-19 Standard Specifications for Arc and
   Flame-Resistant Rainwear. With a TPP of 21.4 cal/cm² and an
   ARC 3 rating: ATPV 28 cal/cm², EBTAS 45 cal/cm², HAF 90%,
   the jacket meets CGSB 155.20-2017 Workwear for Protection
   Against Hydrocarbon Flash Fire FR Rainwear Standard.
- Certification This safety jacket meets CSA Z96-15 Class 2
  Level 2 and Class 3 Level 2 when worn with hi-viz pants with
  reflective stripes on legs and is certified to ASTM F2733-17
  standards for Flame-Resistant Rainwear for Protection Against
  Flame Hazards.
- Visibility The high-visibility orange jacket is fashioned to be tough and flexible. The heat-applied StarTech® FR reflective tape offers superior visibility and safety in low-light conditions and is 100% waterproof.
- Closure Type Designed to be durable and sturdy, the jacket has inner and outer storm flaps/zipper closure with two front pockets with flaps that feature an FR hook-and-loop closure. The angled collar under the chin is also designed with an FR hook-and-loop closure that can fit a rolled-up hard hat-sized hood (sold separately).
- Design The seams of the jacket are vulcanized for superior strength to prevent rips and tears. The dolman sleeve design, the inner elastic cuffs, and the tab style hook-and-loop cuff adjustments provide comfort while allowing users to move and work freely.



## TECHNICAL SPECIFICATIONS

Attributes

Abrasion and Tear Resistant| Chemical Resistant| Fire Resistant| Inherently FR| Oil Resistant| Puncture Resistant|

Waterproof| Windproof, Abrasion Resistant| Puncture Resistant|

Tear Resistant| Waterproof

Certification

CSA Z96-15 Class 2 Level 2| CSA Z462-18, CSA Z96-22 Class 2 Level 2| CSA Z462-18

Closure Type Storm Placket, Storm Placket with Zipper Closure

Colour

Orange, Bright Orange, Hi-Viz Orange

Cuff Adjustment Inner Elastic| Tab-style Hook and Loop

Duty Level For Use

Heavy Duty Foldable Hood in Collar

ARC 3

FR & ARC

with

ASTM F1891-19|
ASTM F2733-17|
ATPV 28 cal/cm²|
CGSB 155.20-2017|
BBTAS 45 cal/cm²| HAF 90%| NFPA 70E-18| TPP 21.4 cal/cm², ARC 3| CSA 2462-18|
CGSB 155.20-2017|
ASTM F1891-19|

F1891-19| ASTM F2733-17| ATPV 28 cal/cm²| EBTAS 45 cal/cm²| HAF 90%| NFPA 70E-18| TPP 21.4 cal/cm² Men

Gender

Hi-Vis CSA Z96-22
Standards Class 2
Level 2
Hood Style Detachable



snap Material

Dupont™ Nomex®| Neoprene

Material Thickness 14 oz/yd²

2

Number of Pockets

Pocket Type

Reflective Tape

Lower Front with Flap and Hook and Loop

StarTech® Flame Resistant

Seam Type Vulcanized

Size Μ

Cold Flex| Detachable Hood Special Features

Waist Adjustment Lower Hem Drawcord