PETRO-GARD® HI-VIS FR/ARC-RATED SAFETY BIB PANTS - HI-VIS ORANGE -



M

Product # V2246750A-M | Model # P160 041A

Safety bib pants designed to keep you comfortable and dry and made using Nomex® threads for flame resistance and optimal arc flash protection.

- Material The Ranpro High Visibility Petro-Gard®
 FR/ARC-Rated Bib Pants are made with 14 oz/yd² low smoke
 Neoprene on Dupont™ Nomex® material, and provides
 superior, heavy-duty 100% waterproof, abrasion-, puncture-,
 and tear-resistant protection.
- ARC and Flame-resistant The fabric of the bib pants meets
 FR ASTM F1891-19 Standard Specifications for Arc and
 Flame-Resistant Rainwear. With a TPP of 21.4 cal/cm² and an
 ARC 3 rating: ATPV 28 cal/cm², EBTAS 45 cal/cm², HAF 90%,
 the pants meet CGSB 155.20-2017 Workwear for Protection
 Against Hydrocarbon Flash Fire FR Rainwear Standard.
- Certification These safety bib pants meet CSA Z96-15 Class 3 Level 2 when worn with a Class 2 Level 2 Jacket and are certified to ASTM F2733-17 standards for Flame-Resistant Rainwear for Protection Against Flame Hazards.
- Visibility The high-visibility orange pants are fashioned to be tough and flexible. The heat-applied StarTech® FR reflective tape offers superior visibility and safety in low-light conditions and is 100% waterproof.
- Design The seams of the pants are vulcanized for superior strength to prevent rips and tears. The single bib design and the adjustable FR hook-and-loop closure leg cuff adjustments allow users to move and work freely.
- Special Features The FR/ARC-Rated Bib Pants feature adjustable arc-resistant fabric suspenders and spreader bar with elastic back and Kwik-Lok connectors to ensure the very best secure hold and all-day comfort to the user. Additionally, the durable reinforced waist ties offer a snug fit.





TECHNICAL SPECIFICATIONS

Adjustment Type Leg FR Hook and Loop| Suspender Buckles| Suspender Kwik-Lok Connectors| Suspender

Spreader
Bar| Waist
Ties, Leg FR
Hook and
Loop|
Suspender
Kwik-Lok
Connectors|
Suspender
Spreader
Bar| Waist

Attributes

Abrasion Resistant| Puncture Resistant| Tear Resistant|

Ties

Resistant| Waterproof, Abrasion and Tear Resistant| Chemical Resistant| Fire Resistant| Inherently FR| Puncture Resistant| Waterproof| Windproof CSA Z96-22

Certification C

Class 3 Level 2, CSA Z96-15 Class 3 Level 2| CSA Z462-18, CSA Z96-22 Class 3 Level 2| CSA

Level 2| CS Z462-18 Hook and

Type Loop
Colour Hi-Viz
Orange,
Orange,
Bright

Closure

Orange

Duty Level Heavy Duty

FR & ARC ARC 3 | CSA

Standards Z462-18|

ARC 3| CSA Z462-18| CGSB 155.20-2017

CGSB
155.20-2017|
ASTM
F1891-19|
ASTM
F2733-17|
ATPV 28
cal/cm²|
EBTAS 45
cal/cm²| HAF
90%| NFPA
70E-18| TPP
21.4 cal/cm²,
ARC 3|
ASTM
F1891-19|
ASTM
F1891-19|
ASTM
F2733-17|
ATPV 28
cal/cm²|
CGSB
155.20-2017|

EBTAS 45 cal/cm²| HAF 90%| NFPA 70E-18| TPP 21.4 cal/cm²

Gender Men

Material Neoprend Dupont^{TN}

Neoprene| Dupont™ Nomex®

Material Thickness 14 oz/yd²

Reflective S

StarTech® Flame Resistant Vulcanized

Seam Type Vulc Size M

Size Range S-4XL Special 100% Features Waterp

100% Waterproof and Windproof

Suspender Type FR Elastic| FR Fabric, FR Fabric