





NEED BELTS FAST? NORTON IS THE RIGHT SOURCE

EXPRESS SERVICE QUALITY

- Made-to-order selection
- Narrow belt lead-times are 2 days
- Wide belt lead-times are 3 days
- Low minimum order quantities
- Standard joints and flexes
- Made in our ISO-certified Stephenville, TX facility

HOW TO PLACE A FASTTRACK ORDER

- Check the FastTrack product availability next page
- Use a full description on your order request:
 Product Size (W x L), Grit Size, Product CAP Code, Quantity
- · Send order electronically, fax, or phone to Customer Service

www.nortonindustrial.com









FastTrack Availability and Lead-time information

WIDTH	GRIT Size	MIN. QTY.	CASE QTY.	MAX. QTY. (EQUALS 2 CASES)	CONVERSION LEAD-TIMES
Narrow Belts					
1/2" through 1"	All	50	200	400	2
Over 1" through 5"	All	10	50	100	2
Over 5" through 9"	All	10	20	40	2
Over 9" through 14"	All	10	10	20	2

WIDTH*	GRIT SIZE	MIN. QTY.	CASE QTY.	MAX. QTY. (EQUALS 2 CASES)	CONVERSION LEAD-TIMES
Wide Belts					
Over 14" through 20"	All	5	10	20	3
Over 20" through 52"	36 & coarser	2	2	4	3
Over 20" through 52"	40-80	3	3	6	3
Over 20" through 52"	100 & finer	5	5	10	3

^{*} FastTrack belt service applies to belts 25" and greater in length

TIER	PRODUCT CAP CODE	SHAPE AVAILABILITY	GRIT SIZE	ABRASIVE GRAIN	BACKING	APPLICATIONS
Vietalwo	rking					
BEST	R980P	Narrow, Wide	24-120	Norton Blaze Ceramic Alumina	Y-wt. Polyester	Latest-generation Norton SG grain, supersized and designed for high-performance grinding on stainless and other alloys
	R984	Narrow, Wide	36-120	Norton SG Ceramic Alumina	Y-wt. Polyester	Norton SG grain for medium-pressure grinding and finishing heat-sensitive alloys
BETTER	R884P	Narrow, Wide	24, 36-80	Norton BlueFire Zirconia Alumina	Y-wt. Polyester	High-performance zirconia alumina grain designed for medium- to high-pressure grinding
	R887D	Narrow, Wide	24, 36-120	Norton BlueFire Zirconia Alumina	Y-wt. Polyester	NEW! Significantly improved-performance zirconia alumina grain, supersized and designed for medium- to high-pressure grinding of heat-sensitive alloys
	R823P	Narrow, Wide	60-220	Norton BlueFire Zirconia Alumina	X-wt. Polyester	High-performance zirconia alumina grain on lighter backing designed for light to medium grinding
GOOD	R766	Narrow	P24-80	Aluminum Oxide Blend	Y-wt. Polyester	Premium aluminum oxide blend product designed for a variety of applications including soft metals to hard-to-grind stainless and carbon steel
	R766X	Narrow, Wide	P60-P400	Norton Neon Aluminum Oxide	X-wt. Polyester	NEW! Quality, P-graded aluminum oxide and broad grit range for stock removal to finer finishing
	MX240	Narrow, Wide	P60-P150	Aluminum Oxide	X-wt. Poly/Cotton	P-graded, heat-treated aluminum oxide X-weight cloth with strong, but flexible, cotton/polyester backing making it an ideal multi-purpose product
	R245	Narrow	P80-P240, P320, P400	Aluminum Oxide	J-wt. Polyester	Aluminum oxide on flexible, lightweight polyester backing for moderate- to light- pressure applications on mild steel
	KF376	Narrow	P80-P320, P400, P600	Aluminum Oxide	J-wt. Cotton	P-graded, heat-treated aluminum oxide with ceramic coating on a very flexible backing for use wherever flexibility and conformability are needed
	R445	Narrow	60-220	Silicon Carbide	X-wt. Polyester	Sharp, silicon carbide grain on medium polyester backing for grinding very hard materials – glass, stone, solid surface
	U243	Narrow, Wide to 12"	X80, X65, X45, X30, X22, X16	Aluminum Oxide	J-wt. Cotton	High-performance, multi-layered NORaX grain on very flexible backing for dry polishing applications
Voodwo	rking					
BEST	R963	Narrow, Wide	24-60, P80, 100-150	Norton SG Ceramic Alumina	Y-wt. Polyester	Norton SG ceramic alumina grain with anti-static coating for forest product applications (MDF, particleboard, plywood)
	R955	Narrow	P36-P120	Norton Red Heat Ceramic Alumina	Y-wt. Cotton	100% ceramic alumina abrasive with Y-weight cloth backing for dimensioning, intermediat sanding of wood
	H975	Narrow, Wide	60-220	Norton Red Heat Ceramic Alumina	F-wt. Paper	NEW! Ceramic alumina grain, antistatic coating, and open coat; the best choice for applications where loading is a problem (soft woods, etc.)
BETTER		Narrow, Wide	24, 36-120	Norton BlueFire Zirconia Alumina	Y-wt. Cotton	Norton BlueFire open-coat product recommended for dry low-pressure applications or where loading is a problem
	H831	Narrow, Wide	24,36-120	Norton BlueFire Zirconia Alumina	F-wt. Paper	Durable zirconia alumina grain, antistatic coating, and open coat: the better choice for applications where loading is a problem (soft woods, etc.)
	H475	Narrow, Wide	P120-P400	Norton Onyx Silicon Carbide	F-wt. Paper	NEW! Sharp silicon carbide and antistatic coating create finer finishes on hard materials and veneers where finish is critical
GOOD	R215	Narrow, Wide	50-180	Aluminum Oxide	X-wt. Cotton	Initial starting specification for all woodworking applications where loading is a problem
	R490	Narrow, Wide	P36-P150	Silicon Carbide	Y-wt. Polyester	Anti-static product for forest product applications (MDF, particle board, plywood) where loading is an issue
	R422	Narrow	50-120	Silicon Carbide	X-wt. Cotton	Initial starting specification for all woodworking applications where loading is not an issue
	H275B	Narrow, Wide	P60-P220	Norton Adalox Aluminum Oxide	F-wt. Paper	NEW! Quality aluminum oxide grain, antistatic coating, and open coat make these an economical choice for all heavy-weight paper belt jobs

Expanded Service to Rolls

*Available in K225, KF376, MX240, R215, R228, R823P

 $www.facebook.com/\textbf{NortonIndustrial} \mid www.youtube.com/\textbf{NortonIndustrial} \mid www.nortonindustrial.com$

USA CUSTOMER SERVICE:

Toll Free Phone: 1 (800) 551-4413 Toll Free Fax: 1 (800) 551-4416 CANADA CUSTOMER SERVICE:

Toll Free Phone: 1 (800) 263-6565 Toll Free Fax: 1 (800) 561-9490 FORM #8308 REV. 10/15

© Saint-Gobain October 2015.

Norton, Adalox, Blaze, BlueFire, Neon, NORaX, Onyx, and Red Heat are registered trademarks; "Reshaping Your World" is a pending trademark; FastTrack is a trademark of of Saint-Gobain Abrasives.





